



Contribution ID: 619

Type: Oral 20 Minutes

## The impact of heterogeneity on the flow and trapping of CO<sub>2</sub> in target UK aquifers

*Monday, 14 May 2018 11:36 (15 minutes)*

The Bunter sandstone formation in the Southern North Sea and the Captain sandstone formation in the Northern North Sea represent two of the largest potential CO<sub>2</sub> stores in the UK, with estimated capacities of up to 14 Gt and 1.7 Gt respectively [1, 2]. With current UK CO<sub>2</sub> emission totalling ~400 Mt/yr [3], the Bunter and Captain formations alone have the potential to store UK emissions for many years.

In order to determine the long-term fate of the injected CO<sub>2</sub> in these systems, accurate characterisation of the multiphase flow behaviour and trapping is needed [4]. Conventionally, multiphase flow functions, namely relative permeability, capillary pressure and trapping, are derived from viscous limit core flood experiments, measured at high flow rates on subsurface rock cores preferentially selected for homogeneity [5], and either used directly in field scale modelling or for further upscaling.

However, for modelling low potential flows characteristic of buoyantly driven CO<sub>2</sub> plume migration, it is important to derive properties that capture the impacts of rock heterogeneity. Sub-metre scale capillary pressure heterogeneities will control local fluid distribution, resulting in equivalent relative permeabilities which are dependent on the flow direction, rock heterogeneity, and the capillary number [6]. Modelling studies have estimated that this can have a significant impact on plume migration and trapping from the mm-km scale [7,8]. However, no experimental protocols have been developed to inform the models with appropriate properties measured on heterogeneous rock samples in the laboratory.

To address the impacts of small scale heterogeneity on large scale flow and trapping of CO<sub>2</sub>, we present a combined experimental and numerical study on rock cores from the Bunter and Captain sandstone formations. We analyse 38 small rock cores covering the entire 100m interval of the Captain D reservoir unit in the Northern North Sea, and a smaller selection of cores taken from the Bunter Sandstone in the Southern North Sea. We use a recently developed characterisation approach [9] to create a 3D numerical model of heterogeneous rock cores, based on laboratory observations. We incorporate hysteresis into the characterisation by building on the recent approach developed by [10]. Once characterised, the numerical cores can accurately predict equivalent relative permeabilities and trapping, dependent on the capillary number and direction of fluid flow.

The numerical models are then used to investigate multiphase flow hysteresis and trapping across the range of conditions estimated to prevail in the CO<sub>2</sub> storage reservoirs. Under these conditions, we systematically explore the impact of hysteresis and heterogeneity on flow and trapping at multiple scales. The migration of CO<sub>2</sub> may be significantly enhanced by heterogeneity when flow can align with the direction of layers. This situation may arise in gravity currents of plumes underneath a confining caprock layer. In contrast, flow is impeded by heterogeneity when the dominant direction crosses bedding layers, as may occur in predominantly upward buoyantly driven migration. In this case, the lowered mobility results in significant spreading of the plume and residual trapping is also enhanced.

## References

- [1] M. Bentham. An assessment of carbon sequestration potential in the UK - Southern North Sea case study. Working Paper 85, The Tyndall Centre for Climate Change Research, UK. 2006.

[2] M. Jin, E. Mackay, M. Quinn, K. Hitchen and M. Akhurst. Evaluation of the CO<sub>2</sub> Storage Capacity of the Captain Sandstone Formation. EAGE Annual Conference & Exhibition incorporating SPE Europec held in Copenhagen, Denmark, 4–7 June 2012.

[3] UK Government. 2015 UK greenhouse gas emissions: final figures - statistical release: National statistics. Department for Business, Energy & Industrial Strategy, viewed 01/12/17. [https://www.gov.uk/government/uploads/system/uploads/attach...](https://www.gov.uk/government/uploads/system/uploads/attachment...)

[4] M.A. Celia, S. Bachu, J. M. Nordbotten, and K. W. Bandilla. Status of CO<sub>2</sub> storage in deep saline aquifers with emphasis on modeling approaches and practical simulations. *Water Resources Research*, 51:6846–6892, 2015.

[5] C. McPhee, J. Reed and I. Zubizaretta. Core analysis: A best practice guide. 64, 2015.

[6] L. Odsæter, C. Berg and A. Rustad. Rate Dependency in Steady-State Upscaling. *Transport in Porous Media*, 110:565-589, 2015.

[7] B. Li and S.M. Benson. Influence of small-scale heterogeneity on upward CO<sub>2</sub> plume migration in storage aquifers. *Advances in Water Resources*, 83:389-404, 2015.

[8] L. Trevisan, P.G. Krishnamurthy and T.A. Meckel. Impact of 3D capillary heterogeneity and bedform architecture at the sub-meter scale on CO<sub>2</sub> saturation for buoyant flow in clastic aquifers. *International Journal of Greenhouse Gas Control*. 56:237-239, 2017.

[9] S.J. Jackson, S. Agada, C.A. Reynolds and S. Krevor. Characterising Drainage Multiphase Flow in Heterogeneous Sandstones. Under review, *Water Resources Research*, 2017.

[10] R. Pini and S.M. Benson. Capillary pressure heterogeneity and hysteresis for the supercritical CO<sub>2</sub>/water system in a sandstone. *Advances in Water Resources*, 108:277-292, 2017.

## Acceptance of Terms and Conditions

[Click here to agree](#)

**Primary author:** JACKSON, Samuel (Imperial College London)

**Co-authors:** Dr REYNOLDS, Catriona (Imperial College London); Dr KREVOR, Sam (Imperial College London)

**Presenter:** JACKSON, Samuel (Imperial College London)

**Session Classification:** Parallel 1-A

**Track Classification:** MS 3.11: fundamental aspects of geological storage of CO<sub>2</sub>