



Contribution ID: 103

Type: Oral Presentation

Lab-scale characterization of a shaly caprock for CO₂ storage: advancements and limitations

Monday, 31 May 2021 18:15 (15 minutes)

The potential of CO₂ underground storage relies on the sealing efficiency of the overlaying caprock that acts as a geological barrier. Shales are extensively studied as potential caprock formations thanks to their favourable hydro-mechanical properties and their sealing capacity: low permeability, high sorption capacity, high swelling ability and high capillary entry pressure. The sealing capacity of a geomaterial is usually quantified based on its measured capillary entry-pressure, i.e. the max. pressure difference that may exist across the interface that separates two immiscible fluids before the non-wetting fluid penetrated the pore space.

The water retention properties of shales have been previously studied in either gas-water or oil-water systems, however, no results for CO₂-water systems are reported to this day. In this work, the capillarity of a shaly caprock geomaterial is investigated with a series of break-through tests (meso-scale). Based on these results, the capillary pressure (P_c) - saturation (S_w) relations of CO₂ displacing water (drainage) and water rewetting (imbibition) are explored and modelled based on the basic principles of unsaturated soil mechanics. The final goal is to project the main findings of the work to possible implications for caprock integrity (entry-pressure) and sealing properties (permeability) for safe CO₂ storage. To this end, the transport properties of the material before and after CO₂ injection are assessed and compared to previous results. The impact of the boundary conditions (pressure and temperature) to the retention, transport and sealing properties of the caprock material are evaluated. The interpretation of the obtained results is supported by an additional series of injection tests, this time in the micro-scale, the kinematics of which are observed and measured locally with in-situ x-ray tomography.

Time Block Preference

Time Block B (14:00-17:00 CET)

References

- Boulin, P. F., Bretonnier, P., Vassil, V., Samouillet, A., Fleury, M., & Lombard, J. M. (2013). Sealing efficiency of caprocks: Experimental investigation of entry pressure measurement methods. *Marine and Petroleum Geology*, 48, 20-30.
- Favero, V., & Laloui, L. (2018). Impact of CO₂ injection on the hydro-mechanical behaviour of a clay-rich caprock. *International Journal of Greenhouse Gas Control*, 71, 133-141.
- Iglauer, S., Al-Yaseri, A. Z., Rezaee, R., & Lebedev, M. (2015). CO₂ wettability of caprocks: Implications for structural storage capacity and containment security. *Geophysical Research Letters*, 42(21), 9279-9284.
- Minardi, A., Stavropoulou, E., Kim, T., Ferrari, A., & Laloui, L. (2021). Experimental assessment of the hydro-mechanical behaviour of a shale caprock during CO₂ injection. *International Journal of Greenhouse Gas Control*, 106, 103225.

Acceptance of Terms and Conditions

[Click here to agree](#)

Newsletter

Student Poster Award

Primary authors: STAVROPOULOU, Eleni (EPFL); Prof. LALOU, Lyesse (EPFL)

Presenter: STAVROPOULOU, Eleni (EPFL)

Session Classification: MS1

Track Classification: (MS1) Porous Media for a Green World: Energy & Climate