InterPore2021



Contribution ID: 552

Type: Oral Presentation

Micro-scale Insights into the Effects of Ionic Strength on CO2 Induced Carbonate Rocks Dissolution

Friday, 4 June 2021 15:00 (15 minutes)

Deep saline aquifers are appropriate for the long-term storage of captured CO2[1]. Low pH environments of deep aquifers due to CO2 injection and dissolution would trigger rock dissolution while the extent of rock dissolution depends on the brine chemistry[2]. Carbonates are the main mineral forming the matrix of carbonate rocks[3]. Moreover, carbonate minerals show higher kinetic reactivity in comparison with alumino-silicate minerals, and therefore, these are the first minerals that react with acidic fluids. Our previous study showed that the brine chemistry affects the extent of carbonate mineral dissolution and consequently, the micro-scale structure and porosity (Φ) of the reservoir rock[2].

Even though it is well known that the aqueous phase in geological reservoirs has ionic strengths ranging up to several hundred g/L, the role of this parameter on geochemical rock-fluid interactions is still a subject of debate in the literature[2][4] due to the variety and complexity of the employed rock and fluid compositions. Thus, this research aims to ascertain the relationship between the alteration of micro-scale pore structure of Indiana limestone, as a common carbonate reservoir rock (>98% calcite) and change in ionic strength of reactive CO2-saturated brine. Three static experiments were designed to evaluate the effect of ionic strength on the amount of CO2-saturated brine induced rock dissolution, using various analytical methods. Brines were synthesized by the most common types of ions[5] which are found in deep aquifers including Na+, K+, Mg2+, Ca2+, and Cl-, to reach ionic strengths from 0 to 0.6 mol/L. Indiana core plugs (with dimensions of 5mm×12mm in diameter and length, respectively) were initially equilibrated with brines for 25 days, based on the geochemical modeling. Then CO2 was injected into hydrothermal batch vessels at a pressure of 130 bar and temperature of 60°C that are representative of subsurface reservoir conditions. Experiments with CO2 saturated brines were continued for 14 days to ensure that desired rock-fluid interactions have occurred. Brine samples (2 mL) were collected at each step to analyze the Ca2+ concentration using inductively coupled plasma-optical emission spectroscopy (ICP-OES) technique.

A Micro-computed tomography (μ -CT) scanner was used as a non-invasive methodology for obtaining information on the spatially resolved three-dimensional pore structure of the rock. Images were acquired with a 4 μ m spatial resolution and X-ray beam of 80 keV and 80 μ A before and after each experiment to evaluate the changes induced by CO2-saturated brine. The alterations of macro-porosity, interparticle sub-resolution micro-porosity, and solid phase of the rock were assessed by μ -CT images. The results of the ICP-OES were used to compare the amount of released Ca2+ in the brine with the calculated volume of dissolved rock by μ -CT images. Overall, results of ICP-OES and μ -CT images illustrate that the extent of rock dissolution and alteration of pore structure of rocks were depending on the ionic strength of the solutions. Therefore, higher ionic strength leads to more rock dissolution. Good agreement was also observed between the total porosity calculated from μ -CT images (Φ = 0.203) and helium porosity measurements (Φ = 0.215).

Time Block Preference

Time Block B (14:00-17:00 CET)

References

[1] Y.-M. Wei et al., "A proposed global layout of carbon capture and storage in line with a 2° C climate target," Nat. Clim. Chang., pp. 1–7.

[2] S. Ghanaatian, O. Shahrokhi, S. Garcia, and M. M. Maroto-Valer, "Understanding Reactive Flow in Porous Media for CO2 Storage Applications," 2019.

[3] O. Shahrokhi, S. Ghanaatian, A. Jahanbakhsh, and M. M. Maroto-Valer, "Effect of Geochemical Integrity of Binding Cement on Sandstone Permeability at Carbon Storage Conditions," 2019.

[4] Y. Min and Y.-S. Jun, "Anorthite Dissolution under Conditions Relevant to Subsurface CO2 Injection: Effects of Na+, Ca2+, and Al3+,"Environ. Sci. Technol., vol. 50, no. 20, pp. 11377–11385, 2016.

[5] R. Jacob and B. Z. Saylor, "CO2 solubility in multi-component brines containing NaCl, KCl, CaCl2 and MgCl2 at 297 K and 1–14 MPa,"Chem. Geol., vol. 424, pp. 86–95, 2016.

Acceptance of Terms and Conditions

Click here to agree

Newsletter

I do not want to receive the InterPore newsletter

Student Poster Award

Primary authors: GHANAATIAN, Shima (Heriot-Watt University); SHAHROKHI, Omid (Heriot-Watt University); Dr GARCIA, Susana (Heriot-Watt University); Prof. MAROTO-VALER, Mercedes (Heriot-Watt University)

Presenter: GHANAATIAN, Shima (Heriot-Watt University)

Session Classification: MS1

Track Classification: (MS1) Porous Media for a Green World: Energy & Climate