



Contribution ID: 363

Type: Oral Presentation

## A Graphical Representation of Membrane Filtration with Adsorption

Wednesday, 2 June 2021 14:45 (15 minutes)

We study the performance of a membrane filter represented by a pore network based on two criteria: 1) total volumetric throughput and 2) accumulated foulant concentration. We first formulate the governing equations of fluid flow on a general network, and we model adsorptive fouling by imposing an advection equation on each pore (edge) and imposing conservation of fluid and foulant volumetric flow rate at each pore junction (vertex), which yields a system of partial differential equations. We study the influence of three geometric network parameters on filter performance: 1) average number of neighbors of each vertex; 2) initial total void volume of the pore network; and 3) tortuosity of the network. We find that total volumetric throughput has a stronger dependence on the initial void volume than on average number of neighbors. Tortuosity turns out to be a universal parameter, leading to almost perfect collapse of all results for a variety of different network architectures. In particular, the accumulated foulant concentration shows an exponential decay as tortuosity increases.

### Time Block Preference

Time Block C (18:00-21:00 CET)

### References

### Acceptance of Terms and Conditions

[Click here to agree](#)

### Newsletter

### Student Poster Award

**Primary authors:** GU, Binan (New Jersey Institute of Technology); Prof. CUMMINGS, Linda (New Jersey Institute of Technology); Prof. KONDIC, Lou (New Jersey Institute of Technology)

**Presenter:** GU, Binan (New Jersey Institute of Technology)

**Session Classification:** MS7

**Track Classification:** (MS7) Mathematical and numerical methods for multi-scale multi-physics, non-linear coupled processes