InterPore2021



Contribution ID: 230

Type: Oral Presentation

Pore-level observation of the transitional pore clogging by asphaltene deposition using micromodels

Monday, 31 May 2021 10:25 (15 minutes)

Asphaltene is defined as the crude oil component, which is soluble in toluene and insoluble in light-n-alkane [1,2]. In the development of oil fields, the deposition of precipitated asphaltene in a reservoir is a serious problem since it leads to clogging of the pores of the rock, resulting in a reduction in permeability [3]. Wang & Civan's model, which was constructed based on DBF (deep-bed-filtration) theory, has been commonly used in Darcy-scale simulations to calculate the volume of asphaltene deposition [4,5]. In this model, the deposition rate of asphaltene is expressed by the summation of three terms: surface deposition caused by adsorption or gravity sedimentation, entrainment, and clogging of pores. Each term contains an empirical coefficient that needs to be tuned by comparing the experimentally measured permeability and the calculated one [6], which means that these coefficients cannot be determined without experiment. Pore-scale observation of the deposited asphaltene can directly evaluate the types of deposition. The observation using X-ray microtomography showed that the cluster of deposited asphaltene clogged multiple pores after flooding with crude oil, which contains asphaltene, into a rock [7]. Although this shows the actual behaviour of the deposition, the transition of the clogging is still unknown. Several studies have been conducted with microfluidics experiments to capture the transient flow inside a transparent chip by a microscope. The process from precipitation to deposition of asphaltene at the wall of the chip [8] or dissolving behaviour of the asphaltene [9] have been visualised. However, the deposition process to clog the pores and the contribution of each type of deposition to the clogging is not well investigated.

In this study, the transition of asphaltene deposition inside porous media was visualised by a glass-made micromodel. In the micromodel, a lattice-like pore-network area with 6 cm in length and 1 cm in width was chemically etched. Each pore size was 100 μ m in width and 110 μ m in depth. Crude oil was mixed with n-heptane as a precipitant of the asphaltene and injected into the micromodel at a rate of 0.7 ml/h, which was equivalent to a Darcy velocity of $1.94 \times 10-4$ m/s. During the injection, the area composed of 2.5 mm length and 1.8 mm width was monitored with a microscope with a ten magnification lens to obtain two-dimensional sequential images. Image analysis was conducted to identify deposited asphaltene.

We observed transitional processes from the deposition of asphaltene particles to the clogging of the pore spaces. At the initial stage, the deposition occurred at the local site of the pores. The deposited site grew by the accumulation. Finally, these local clusters were connected, resulting in the complete clogging of the area. The area of occupancy of the pores clogged with asphaltene linearly increased to 57.6%.

The ratio of deposition type to total deposition area was evaluated quantitatively to investigate each type's contribution to the permeability reduction.

Time Block Preference

Time Block A (09:00-12:00 CET)

References

[1] Mitchell, D. L. and Speight, J. G. (1973). The solubility of asphaltenes in hydrocarbon solvents. Fuel, 52(2), 149–152. http://doi.org/https://doi.org/10.1016/0016-2361(73)90040-9.

[2] Buenrostro-Gonzalez, E., Groenzin, H., Lira-Galeana, C. and Mullins, O. C. (2001). The overriding chemical principles that define asphaltenes. Energy and Fuels, 15(4), 972–978. http://doi.org/https://doi.org/10.1021/ef0100449.
[3] Hamadou, R., Khodja, M., Kartout, M., & Jada, A. (2008). Permeability reduction by asphaltenes and resins deposition in porous media. Fuel, 87(10–11), 2178–2185. https://doi.org/10.1016/j.fuel.2007.12.009
[4] Gruesbeck, C. and Collins, R. E. (1982). Entrainment and Deposition of Fine Particles in Porous Media. Society of Petroleum Engineers Journal, 22(06), 847–856. https://doi.org/10.2118/8430-pa.

[5] Wang, S., and Civan, F. (2005). Modelling formation damage by asphaltene deposition during primary oil recovery. Journal of Energy Resources Technology, Transactions of the ASME, 127(4), 310–317. https://doi.org/10.1115/1.1924465.
[6] Behbahani, T. J., Ghotbi, C., Taghikhani, V. and Shahrabadi, A. (2013). Experimental Study and Mathematical Modeling of Asphaltene Deposition Mechanism in Core Samples. Oil and Gas Science and Technology, 70(6), 1051–1074. https://doi.org/10.2516/ogst/2013128.

[7] Lin, Q., Akai, T., Blunt, M. J., Bijeljic, B., Iwama, H., Takabayashi, K., Onaka, Y. and Yonebayashi, H. (2020). Pore-scale imaging of asphaltene-induced pore-clogging in carbonate rocks. Fuel, 286(2021), 118871. https://doi.org/10.1016/j.fuel.2020.118871.

[8] Doryani, H., Malayeri, M. R., & Riazi, M. (2016). Visualization of asphaltene precipitation and deposition in a uniformly patterned glass micromodel. Fuel, 182, 613–622. https://doi.org/10.1016/j.fuel.2016.06.004
[9] Lin, Y. J., He, P., Tavakkoli, M., Mathew, N. T., Fatt, Y. Y., Chai, J., C., Goharzadeh, A., Vargas, F. M., Biswal, S. L. (2016). Examining Asphaltene Solubility on Deposition in Model Porous Media. Langmuir, 32(34), 8729–8734. http://doi.org/10.1021/acs.langmuir.6b02376.

Acceptance of Terms and Conditions

Click here to agree

Newsletter

I do not want to receive the InterPore newsletter

Student Poster Award

Primary author: Ms ONAKA, Yutaka (The University of Tokyo/Japan Oil, Gas and Metals National Corporation (JOGMEC))

Co-author: Prof. SATO, Kozo (The University of Tokyo)

Presenter: Ms ONAKA, Yutaka (The University of Tokyo/Japan Oil, Gas and Metals National Corporation (JOGMEC))

Session Classification: MS11

Track Classification: (MS11) Microfluidics in porous systems