InterPore2021



Contribution ID: 7

Type: Oral Presentation

# Digital Rock Analysis of Low Resistivity Pay Zones to Refine Saturation

Tuesday, 1 June 2021 14:40 (15 minutes)

Low resistivity pays (LRPs) are reservoirs from which dry hydrocarbons are produced in the presence of erroneously interpreted water saturations. LRPs are often identified within laminated reservoir sequences, shaley lithologies, and formations with multi-modal pore-size characteristics or containing fresh formation waters identified on the basis of well logging, testing and core observations. The following study addresses the characterization of a microporous carbonate LRP formation using digital rock physics (DRP) analysis in various facies identified in 62 core plugs through digital imaging.

A comprehensive DRP workflow was utilized to produce 3D digital rock models of rock samples through multi-resolution X-ray tomographic imaging and application of a machine-learning algorithm to characterize the internal fabric of the rock samples based upon the abundance of microporosity. The physical samples were also analyzed using mercury injection capillary pressure (MICP) to allow calibration and validate the 3D digital rock models. Numerical simulation of the electrical current flow through the samples showed the variation of Archie's saturation exponent "n"with water saturation, i.e., the increasing influence of the microporous regions as water saturation is decreased. The meso- and macro-pores were found to produce the moveable hydrocarbons due to their lower capillary pressure; the micro-pores holding immobile formation water. The DRP models were then used to simulate the drainage relative permeability curves to identify the water saturation causing the first water in-flow, and separate immobile and free-fluids. The wireline logs saturation profile was updated with these results.

As shown by digital experiments, conducted on LRP the water-filled micro-pores provide a continuous path for electric current, masking the hydrocarbons and overestimating the water saturation. Saturation calculation could be significantly refined, if LRP wireline petrophysical models are calibrated using DRP data incorporating the modelled Archie's saturation exponent and first water in-flow from relative permeability curves.

### **Time Block Preference**

Time Block A (09:00-12:00 CET)

#### References

## Acceptance of Terms and Conditions

Click here to agree

#### Newsletter

Primary authors: Dr DESHENENKOV, Ivan (Saudi Aramco); Mr FURAISH, Aqeel; Mr ALHILAL, Hussain

Presenter: Dr DESHENENKOV, Ivan (Saudi Aramco)

Session Classification: MS9

Track Classification: (MS9) Pore-scale modelling