



Contribution ID: 98

Type: Oral Presentation

Simulation of CO₂ mineral trapping and permeability alteration in fractured basalt: Implications for geologic carbon sequestration in mafic reservoirs

Thursday, 2 June 2022 13:30 (15 minutes)

Basalt formations are potentially attractive targets for carbon capture and sequestration (CCS) on the basis of favorable CO₂-water-rock reactions, which result in permanent CO₂ isolation through mineral trapping. Recent

pilot-scale experiments in Iceland and Washington state, USA, provide promising results that indicate rapid carbon mineralization occurs within basalt reservoirs. Nevertheless, transitioning these pilot-scale results to large-scale industrial CCS operations is fraught with uncertainty because fluid flow in basalt formations is governed by fracture-controlled hydraulic properties that are highly heterogeneous and difficult to map in situ.

This uncertainty is exacerbated by feedbacks between multi-phase fluid dynamics (CO₂ and water) and fluid-rock

reactions, which may result in a reinforcing feedback comprising CO₂ mineralization, permeability alteration, and fluid mobility. To begin to understand the feedbacks between multi-phase fluid flow and mineralization in

fractured basalt, this study uses reactive transport simulation methods to model CO₂ infiltrating a meter-scale, synthetic basalt fracture overlying a storage reservoir while accounting for porosity change due to mineralization

and its corresponding effect on permeability and fluid mobility. Results show that (i) carbonate and clay mineralization tends to occur downgradient of a fracture intersection, (ii) mineralization reduces porosity, which

leads to permeability reduction and slows free-phase CO₂ migration, (iii) stronger porosity-permeability coupling

increases the proportion of mineralized carbon while reducing CO₂ mass that can enter fracture, which may lead

to self-sealing behavior as fluid mobility approaches nil, and (iv) errors caused by unknown porosity-permeability

relationships are small in comparison to errors that arise by omitting mineralization-induced permeability reduction when simulating CO₂ sequestration scenarios in basalt reservoirs.

Acceptance of the Terms & Conditions

[Click here to agree](#)

MDPI Energies Student Poster Award

No, do not submit my presentation for the student posters award.

Country

US

References

Time Block Preference

Time Block C (18:00-21:00 CET)

Participation

Online

Primary authors: WU, Hao (Los Alamos National Laboratory); JAYNE, Richard (Sandia National Laboratory); BODNAR, Robert (Virginia Tech); POLLYEA, Ryan (Virginia Tech)

Presenter: WU, Hao (Los Alamos National Laboratory)

Session Classification: MS03

Track Classification: (MS03) Flow, transport and mechanics in fractured porous media