



Contribution ID: 829

Type: **Poster Presentation**

Laboratory scale demonstration of asbestos mobility in sandy aquifer systems

Tuesday, 23 May 2023 16:10 (1h 30m)

Asbestos is a well-known and regulated air pollutant and it is indeed classified as a carcinogenic compound of the first group. However, several studies recently reported asbestos presence also in fresh water sources, such as lakes, rivers, groundwater and drinking water. As far as human exposure, two main pathways can be identified for waterborne asbestos: (i) inhalation due to water evaporation and subsequent fibre dispersion into air; (ii) ingestion mainly via drinking water. For the first case, the concentration limits (number per litre of longer than 5 μm fibres) established for air must be respected, i.e. 100 f/L at workplaces (U.S. Occupational Safety and Health Administration) and 1 f/L in outdoor environments (World Health Organization). As for oral exposure, the effects of asbestos ingestion on human health are still not well known; however, the U.S-Environmental Protection Agency established a precautionary concentration limit for longer than 10 μm fibres in drinking water of $7 \cdot 10^{-6}$ f/L.

Focussing on groundwater contamination, asbestos fibres can typically be found in areas where water flows through aquifers containing Naturally Occurring Asbestos or in the proximity of mines and mine tailing deposits. The abovementioned contamination scenarios can represent a severe environmental and sanitary issue due to the potential capability of asbestos to migrate through aquifer systems. However, until now asbestos has been considered substantially immobile in groundwater since its shape and surface charge are expected to result in irreversible filtration of the fibres upon release into the aquifer. Therefore, no studies have investigated in depth the mechanisms governing the asbestos subsurface mobility so far.

This laboratory scale work studied the transport of crocidolite, a negative charged amphibole asbestos, through quartz sandy aquifers. Two sets of column tests were performed varying the concentration of the injected asbestos suspension, the sand grain size distribution and the water pH. The asbestos concentration in water was measured at the column inlet and outlet using a UV-vis spectrophotometer and the fibre number, size and shape were characterized through SEM-EDS analysis.

The results demonstrated that crocidolite asbestos is not actually immobile and can potentially flow through sandy porous media. As expected, fibre retention was higher in the finer sand, even if the grain size influence was found to be more pronounced when increasing asbestos concentration in the injected suspension. Interestingly, the study showed that asbestos deposition is not completely irreversible, since a fraction of the filtered fibres was remobilized after the column was flushed with high pH water. As for morphological characterization, small fibres proved more mobile than the long ones: several fibres with length $> 5 \mu\text{m}$ (carcinogenic when respired) were collected at the column outlet, whereas most of the fibres longer than 10 μm were filtered out by the porous medium. These results suggest that the air dispersion of waterborne fibres is expected to be the most likely and impacting scenario. Future studies should therefore aim at confirming the effective crocidolite mobility also in real environments.

Participation

In-Person

References

MDPI Energies Student Poster Award

Yes, I would like to submit this presentation into the student poster award.

Country

Italy

Acceptance of the Terms & Conditions

[Click here to agree](#)

Energy Transition Focused Abstracts

Primary author: Dr MAGHERINI, Leonardo (Politecnico di Torino)

Co-authors: AVATANEO, Chiara; CAPELLA, Silvana; LASAGNA, Manuela; BIANCO, Carlo (Politecnico di Torino - DIATI); BELLUSO, Elena; DE LUCA, Domenico; SETHI, Rajandrea (Politecnico di Torino)

Presenter: Dr MAGHERINI, Leonardo (Politecnico di Torino)

Session Classification: Poster

Track Classification: (MS18) Innovative Methods for Characterization, Monitoring, and In-Situ Remediation of Contaminated Soils and Aquifers