### InterPore2023



Contribution ID: 420

Type: Oral Presentation

# Non-linear flow phenomena in a porous cylindric microtube

Monday, 22 May 2023 14:45 (15 minutes)

The understanding of water transfer in heterogeneous porous media such as soils is at the center of many issues such as water resource management. In the macroporosity as opened cracks, earthworm burrows free surface flow can be a dominant (Sammartino et al., 2012). Very little is known about the physical processes involved in infiltration, whether it is the form of streamflow, continuous films in the macropore (Keven and Germann, 2013) or the "active" macroporosity during a flow and also the exchange mechanisms at the macropore interface (Katuwa et al., 2015). Answering these questions on a small scale is crucial because, for example, the filling rate of a macropore is closely related to colloid filtering, water retention phenomena. The last decades many models have been developed to model flow in macroporosity such as dual porosity with Kinetik Dispersive Waves models (Di Pietro et al., 2013) or conceptual approaches to film flow as in Nimmo et al. (2010). However, these models still do not explain all of the observed flows made by imaging techniques (Sammartino et al., 2015; Lissy, 2019).

In this paper, we focus on the modelling and simulating free surface flow in a cylindrical microtube taking into account the physicochemical properties of the matrix and at the interface between the matrix and the macropore. Indeed, organic matter is known to generally impart hydrophobic properties to soils. In an impervious microtube surface, a rich range of flow shapes has been identified: droplets, thin films or rivulets and notably, there is a regime leading to complete wetting (Beltrame, 2018). In the present work, the mesopore surface is porous and fluid transfer may appear through the interface between the macropore and the soil matrix.

The model is based on the long-wave approximation with a free surface. The soil matrix wettability is taking into account using disjoining and conjoining pressures as presented in Beltrame (2019). The linear classical flux condition on the liquid/porous interface as used in Ding and Liu (2011) does not yield if a hydrophobic coating is present: the flux depends on the matrix moisture too (Doerr et al., 2000). Our present model takes into account wettability at the surface and also in the porous matrix (Beltrame and Cajot, 2022). Thus, the dynamics, both in the matrix and in the macropore, are governed by a gradient type equation (Thiele, 2018) where free energy terms characterize the wettability.

Using numerical simulation and bifurcation diagrams, a rich behavior is brought to light. Notably, several flow regimes in a microtube are in competition and complex spatial organization appears showing clusters of annular drop trains. In addition, the interaction between the flow in micro-tube and the imbibition in porous matrix leads to non-linear phenomena. In particular, decreasing the saturation in the porous matrix may slightly increase the flow rate in the microporosity for specific parameters. This non-linear analysis highlights the crucial role of wettability in the fluid transfer.

#### **Participation**

In-Person

#### References

Beltrame (2018), "Partial and complete wetting in micro-tube," Europhysics Letters 121, 64002.

Beltrame (2019), "Soils as a Key Component of the Critical Zone 3: Soils and Water Circulation"ISTE, Bourrié (Ed.) "Soil wettability" pp. 53–82.

Beltrame and Cajot (2022), "Model of hydrophobic porous media applied to stratified media: Water trapping, intermittent flow and fingering instability,"Europhysics Letters 138, 53004.

Ding and Liu (2011), "Stability of liquid films on a porous vertical cylinder", Phys. Rev. E 84, 046307

Doerr et al. (2000), "Soil water repellency: its causes, characteristics and hydro-geomorphological significance "Earth-Science Reviews 51.

Lissy (2019) . « Imagerie quantitative non invasive et expérimentation pour l'intégration des phénomènes d'écoulement non - uniforme dans les modèles de transfert de masse en milieux poreux hétérogènes - Application aux sols structurés » PhD thesis, Avignon Université, Avignon.

Nimmo et al. (2010), « Theory for Source-Responsive and Free-Surface Film Modeling of Unsaturated Flow » Vadose. Zone. J. 9, pp. 295–306.

Sammartino et al. (2012) "A novel method to visualize and characterize preferential flow in undisturbed soil cores by using multislice helical ct"Vadose Zone Journal, 11(1).Vadose. Zone. J. 11 (2012).

Sammartino et al. (2015). "Identifying the functional macropore network related to preferential flow in structured soils" Vadose Zone J., 14(10).

Thiele (2018). Recent advances in and future challenges for mesoscopic hydrodynamic modelling of complex wetting. Colloids and Surfaces A, 553:487–495.

# **MDPI Energies Student Poster Award**

No, do not submit my presenation for the student posters award.

# Country

France

## Acceptance of the Terms & Conditions

Click here to agree

## **Energy Transition Focused Abstracts**

**Primary authors:** Mr CAJOT, Florian (UMR1114 EMMAH, INRAE - Avignon Université); BELTRAME, Philippe (Avignon Université)

Presenter: BELTRAME, Philippe (Avignon Université)

Session Classification: MS21

Track Classification: (MS21) Non-linear effects in flow and transport through porous media