



Contribution ID: 793

Type: Oral Presentation

Dynamics of two-phase flow in coal using X-ray micro-computed tomography imaging and positron emission tomography

Thursday, 16 May 2024 09:20 (15 minutes)

The fluid dynamics of gas-brine flow within porous media play a crucial role in the recovery of hydrocarbon gas and the sequestration of CO₂. Coal seams are targeted as a reservoir rock because of their strong adsorption properties. However, permeability is an issue as they consist of matrix and fracture components, present a complex flow channel system for competing fluids and gases. During production, the initial dewatering process reduces pressure and induces CH₄ desorption from the matrix into fractures, accompanying brine flow towards production wells. CO₂ injection further displaces CH₄ and stores CO₂ in the matrix due to competitive adsorption with CH₄. Moreover, Coal seams are dynamic during gas depletion and successive injection as the matrix shrinks and then swells, altering the structure of the flow channels. This introduces additional complexity to the transportation behaviour of the fluids. This study introduces an innovative approach to investigate the dynamics of gas-water two-phase flow within fractured coal cores. The methodology involves an integration of unsteady-state two-phase fluid flow experiments, dynamic positron emission tomography (PET) imaging, and high-resolution X-ray micro-computed tomography (micro-CT) imaging. Under reservoir pressure conditions, micro-CT imaging is employed to capture the fracture structure of the coal sample. A gas-injection-based unsteady-state flooding test is subsequently conducted on a water-saturated sample at the same pressures, with PET scanning used for dynamic imaging of the displacement process. This flooding experiment is designed to emulate gas-water transport behaviour in a coal seam during production, facilitating real-time data collection of gas injection volume, inlet-outlet differential pressure variations, and water production. The obtained data is utilized to predict the relative permeability curves of the sample. Following the flooding experiment, a multi-scale image analysis is performed by aligning low-resolution PET images at different time steps with the high-resolution micro-CT image. It superimposes the flow path onto the fracture structure of the sample, allowing for the determination of water saturation and characterization of flow behaviour. This analysis leverages the unique advantages of PET's dynamic imaging capabilities and micro-CT's high image resolution to enhance the visualization of fluid transportation behaviour within the media. Overall, this approach offers significant potential for sensitivity analysis on relative permeability of a porous media, including not only coal, but also reservoir rocks like sandstone and shale. It can consider factors such as stress, temperature, and wettability, enabling a quantitative comparison of relative permeability and offering visual insights into fluid flow behaviour as conditions change. This contributes to precise predictions of relative permeability, aiding in the identification of optimal scenarios for both hydrocarbon exploitation and carbon sequestration.

Acceptance of the Terms & Conditions

[Click here to agree](#)

Student Awards

I would like to submit this presentation into the MDPI student poster award.

Country

Australia

Porous Media & Biology Focused Abstracts**References****Conference Proceedings**

I am not interested in having my paper published in the proceedings

Primary authors: Prof. ESTERLE, Joan (University of Queensland); MOSTAGHIMI, Peyman; ARMSTRONG, Ryan; XI, Wen (UNSW); JING, YU

Presenter: XI, Wen (UNSW)

Session Classification: MS03

Track Classification: (MS03) Flow, transport and mechanics in fractured porous media