

# 1st Iran InterPore Conference



## Report of Contributions

Contribution ID: 4

Type: **Poster Presentation**

## The study of drug release processes: modeling

The advent of drug delivery systems has garnered considerable attention from researchers as a novel method for drug delivery. Among the advantages of such systems is the gradual release of drugs at a constant rate, which significantly reduces the frequency of drug administration and associated adverse effects.

This article aims to provide a comprehensive review of existing mathematical models which correspond to the known drug release mechanisms, classified as diffusion-, swelling-, and erosion-controlled systems. The modeling of drug transport through drug release systems involving chemical reactions and polymer erosion on the skin has been investigated for transdermal drug delivery systems. A mathematical model has been developed to predict the drug release rate and the position of the moving boundary layer within the system at any moment.

The presented model, considering linear and nonlinear changes in polymer matrix erosion, has been semi-analytically solved using the Galerkin and Lee methods; The outcome provides curves illustrating the relationship between the drug release rate, the amount of drug released, the position of the moving boundary, and system performance over time.

The results indicate that the drug release rate and the amount of drug released, augment with the increase in the ratio of the reaction rate constant to the diffusion coefficient and the initial drug concentration. Additionally, the system performance time decreases as the ratio of the reaction rate constant to the diffusion coefficient and the initial drug concentration increases. The solution of the presented model using the Galerkin and Lee methods yields similar results.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** Ms DEGHAN, Shiva

**Presenter:** Ms DEGHAN, Shiva

**Track Classification:** New Energies / Underground Gas Storage

Contribution ID: 5

Type: **Poster Presentation**

## **Injection and storage of carbon dioxide gas in depleted oil and gas reservoirs in order to enhance oil recovery and preserve the environment**

Lately, the increasing discharge of greenhouse gases from burning fossil fuels has brought irreversible environmental damage, and global warming has been triggered by this environmental problem. The greenhouse gases, particularly carbon dioxide, have become the primary reason for global warming. Consequently, carbon dioxide has become an environmental pollutant of a grave nature and deserves careful analysis, as it has such an important role in the climate change processes. As a result, researchers have come up with a number of potential strategies, one of which is injecting carbon dioxide into depleted oil and gas reservoirs. Research projects have identified that the rock cap used for containing oil and gas in past events can be re-used to restrain the newly introduced carbon dioxide and would stop upward migration. Depleted oil and gas reservoirs offer superior geologic storage opportunities compared to deep saline reservoirs. A key component to the potential storage capacity of the reservoirs is to understand the ideal pressure to inject carbon dioxide, a matter pertinent to reservoir engineers. In fact, the injection and storage of carbon dioxide in depleted oil and gas reservoirs not only contributes to reducing greenhouse gases but can also potentially benefit in enhancing oil recovery from depleted reservoirs, ultimately achieving a profitable economic level for the oil-producing country.

Keywords: greenhouse gases, carbon dioxide, depleted reservoirs, storage, enhancing oil recovery

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** Mr BEHNAM MOTLAGH, Mohammad Amin (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran); Mr TANHAEI, Hadi (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Co-author:** Mr SAEEDI DEHAGHANI, Amir Hossein (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Presenter:** Mr BEHNAM MOTLAGH, Mohammad Amin (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 6

Type: **Oral Presentation**

## **Investigation of natural surfactants in interaction with divalent ions and their effects on the environment**

*Tuesday, 24 September 2024 09:45 (15 minutes)*

Although the realm of water and gas injection within enhanced oil recovery has garnered considerable attention in the contemporary era, some engineers believe that alternative and cost-effective methods could play a more pivotal role in this field. Utilization of substances like surfactants and polymers is seen as an innovative technique that has made a substantial impact on the oil sector; however, the large-scale production of such materials proves to be financially burdensome. Furthermore, the manufacture of these substances results in hazardous wastes, posing risks to both human health and the environment, ultimately leading to extensive and irreversible pollution. The adoption of natural surfactants emerges as a viable solution with relatively high efficacy. These plant-derived surfactants, extracted from indigenous plant leaves, are cost-effective, biodegradable, and pose no threat to human health or the environment. The incorporation of these natural surfactants in oil-related experiments has yielded satisfactory outcomes, showcasing their effectiveness in reducing the interfacial tension between water and oil, modifying crude oil viscosity, enhancing the extraction rate of asphaltene, and isolating heavy components of crude oil.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** SANIEE, mohammadreza (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Co-author:** SAEEDI DEHAGHANI, Amir Hossein (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Presenter:** SANIEE, mohammadreza (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Session Classification:** Parallel Session 1

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 8

Type: **Oral Presentation**

## Investigating Cohesion Influence on Fine Particle Transport via Pore Doublet Model A CFD-DEM Analysis

*Tuesday, 24 September 2024 10:00 (15 minutes)*

This research delves into the transportation of micro-sized particles within a doublet pore model featuring two distinct pore throat sizes. To simulate a two-phase particle-fluid suspension, the CFD-DEM method is employed, combining the Navier-Stokes equation with Newton's second law of particle motion. Cohesion forces between particles and pore throats are characterized using the Simplified Johnson-Kendall-Roberts (SJKR) contact model, which is applied in our simulation to identify locations of agglomerations. Results reveal that altering cohesive energy density, from  $10,000 \text{ J/m}^3$  to  $100,000 \text{ J/m}^3$ , significantly increases the likelihood of agglomeration in the smaller pore throat. It becomes evident that areas in close proximity to the throats are the most prone to particle agglomerations, leading to pressure drops over time. The formation of particle clusters within the pore throats intensifies with both an increase in the number of particles and fluid velocity from  $0.001 \text{ m/s}$  to  $0.01 \text{ m/s}$ . Nevertheless, low flow rates ( $0.001 \text{ m/s}$ ) are insufficient to mitigate blockages.

### Student presentation contest

Opt in

### Journal Submission

Not Interested

### Student Poster Contest

Opt In

**Primary author:** Mr GHODSI, Mohammad (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Co-author:** Dr RASAEI, Mohammad Reza (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Presenter:** Mr GHODSI, Mohammad (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Session Classification:** Parallel Session 1

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 9

Type: **Oral Presentation**

## Exploring the Influence of Porous Media Morphology and Capillary Number on Immiscible Oil Recovery

*Tuesday, 24 September 2024 09:45 (15 minutes)*

Pore-scale simulation and analysis of oil displacement in digital rocks has shown great promise in tracking oil recovery in porous media. This paper examines three digital rocks with varying pore and throat radii but the same porosities, studying their behavior under immiscible oil recovery through waterflooding. Computational fluid dynamics was used to conduct numerical simulations to observe the impact of rock morphology on breakthrough times, residual oil saturations, and oil displacement patterns. The validity of the simulation mechanism is confirmed in both imbibition and drainage conditions through the pore doublet Chatzis' experiment. This study consisted of 33 separate simulations which varied in mobility ratios, interfacial tensions, and injection velocities. The findings suggest that smaller pore and throat radii result in higher oil recovery and water percolation and faster breakthrough times that facilitates the effects of viscous fingering. An increase in capillary number was found to have a significant impact on oil recovery in larger pores and throats.

### Student presentation contest

Opt in

### Journal Submission

Not Interested

### Student Poster Contest

Opt In

**Primary author:** Mr GHODSI, Mohammad (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Co-author:** Dr RASAEI, Mohammad Reza (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Presenter:** Mr GHODSI, Mohammad (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Session Classification:** Parallel Session 2

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 10

Type: **Oral Presentation**

## The Relationship between Pore Types and Reservoir Flow Units in a Heterogeneous Carbonate Reservoir

*Tuesday, 24 September 2024 10:00 (15 minutes)*

Heterogeneity in carbonate reservoirs, originating from various depositional, diagenetic, and fracturing processes, presents a significant challenge in identifying flow units and reservoir zonation. In this study, to identify the main productive units and understand the relationship between the pore nature and their role in development of different reservoir zones, core data and petrophysical logs from a well were used. Based on the modified Lorenz Plot, the reservoir rock was initially divided into 10 reservoir units. Reservoir heterogeneity assessments indicated that some zones still exhibit high heterogeneity. Therefore, using other methods such as cumulative permeability plot, normalized cumulative reservoir quality index, and calculation of pore throat radius, the identified zones were further divided into 20 sub-zones or flow units: high-speed, baffle, and barrier flow units.

The high-speed flow units (eight units), which approximately have a cumulative thickness of about 102 meters and contribute to over three-quarters of the well's production, correspond to dolomitized grainstone facies with interparticle and intercrystalline pores and an average pore throat radius of over 5 microns (macro and megapores). The baffle units correspond to grainstones with oomoldic porosity and predominantly dolomitized mud-dominated facies with pore sizes less than one micron (meso- and micropores). The barrier units, contributing less than one percent to the well's production, account for one-third of the reservoir rock thickness and predominantly correspond to low-porosity facies of reservoir units K3 and K1 and extend near the Permo-Triassic boundary sequence.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** ESRAFILI-DIZAJI, Behrooz (Assistant Professor, Department of Petroleum Exploration at University of Tehran)

**Co-author:** Mr POURRAHMAT, Mohamad (Student)

**Presenter:** Mr POURRAHMAT, Mohamad (Student)

**Session Classification:** Parallel Session 2



**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 11

Type: **Poster Presentation**

## **A review of the application of image processing in porous media**

Nowadays, the study of fluid flow and transfer phenomena in porous media has received much attention due to its importance in industrial, engineering, biological and environmental applications. Geometry, cavity space and topology are among the key characteristics of porous media. These components play an important role in determining the characteristics of the porous medium. Image processing, as one of the sub-branches of artificial intelligence and machine learning, has unique capabilities in image analysis. Image recognition is becoming a very important step in most problem solving systems in the modern world. There are many methods of image acquisition, analysis and classification available. Image processing methods and algorithms are satellite and remote imaging, video images, 3D images. In porous environments, image processing can help to separate and identify materials in the environment, calculate physical parameters such as density, weather in the environment, improve processes related to porous environments, etc. Image processing in porous environments is a powerful tool for analyzing and recognizing the characteristics of the environment. In this research, the studies conducted in the field of porous media and various applications of image processing in porous media have been discussed. Image processing-based measurement techniques have the advantages of non-destructive, easy operation, deep 3D visibility and high resolution. The application area of porous materials can be extended by using suitable imaging techniques. Image processing techniques include image alignment, image stitching, contrast enhancement, thresholding, image separation, 3D reconstruction, etc. The use of these materials is strongly influenced by the properties of the measured materials. Image processing methods can be transferred to other areas with similar image characteristics. To achieve accurate results, image processing-based measurement needs to be improved in terms of hardware, testing, and image processing algorithms.

### **Student presentation contest**

Not Interested

### **Journal Submission**

Not Interested

### **Student Poster Contest**


Not Interested

**Primary authors:** AKBARZADEH, Alireza; Dr AGHDASINIA, Hassan; Dr AHMADLOUYDARAB, Majid

**Presenter:** Dr AGHDASINIA, Hassan

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 12

Type: **Oral Presentation***Tuesday, 24 September 2024 09:45 (15 minutes)*

This study focuses on the characterization of reservoir rock characteristics to improve hydrocarbon recovery, groundwater management, and geothermal energy extraction. Traditional methods for determining properties such as porosity, permeability, and pore size distribution are often labor-intensive and time-consuming. Instead, this research uses a pore network model to simulate and analyze fluid flow in porous networks. This study describes the process of creating digital pore network models from microCT images, calibrating them with experimental data, and extracting petrophysical properties through simulation. Analysis of a carbonate rock formation shows a porosity of 14.03%, which indicates limited pore space for fluid storage and flow. The tortuosity value of 2.96 indicates a complex pore network that prevents fluid movement. Despite the low formation resistance factor (0.2), which implies good continuity, the molar flow rate is low, which corresponds to the reduction of effective porosity. 1.00046 ohm meter as rock resistance and 0.20009 ohm meter indicates the presence of hydrocarbon. The effective release value of 2.1879 is an effective factor in fluid extraction due to the inherent properties of the reservoir, which causes the level of this parameter to be low. Overall, these findings indicate that the reservoir has limited productivity, which requires improved mining techniques.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Not Interested

**Primary author:** PILEHKOUHI, Mohammadreza (Student)**Co-author:** Dr SADEGHNEJAD, Saeid (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)**Presenter:** PILEHKOUHI, Mohammadreza (Student)**Session Classification:** Parallel Session 4**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 13

Type: **Poster Presentation**

## Direct numerical simulation of single-phase fluid flow in two-dimensional porous media

The present study investigates the simulation of incompressible fluid flow of water using the OpenFOAM software in a porous medium. The solid phase is imported into the software via an “.stl” file format, and the solid region is extracted from the raw geometry utilizing the snappyHexMesh utility. To analyze the problem in two dimensions, a single cell layer is generated perpendicular to the plane. Subsequently, a mesh study is conducted, and an optimal mesh is selected. The results indicate that a pressure drop of one pascal is established between the inlet and outlet under laminar flow conditions. Furthermore, as the cross-sectional area available for flow decreases, the fluid velocity increases.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** POURFAROKH, Mohammad Reza (School of Mechanical Engineering, Iran University of Science and Technology, 16846-13114, Tehran, Iran)

**Co-author:** YOUSEFI, Soroush (School of Mechanical Engineering, Iran University of Science and Technology, 16846-13114, Tehran, Iran)

**Presenter:** POURFAROKH, Mohammad Reza (School of Mechanical Engineering, Iran University of Science and Technology, 16846-13114, Tehran, Iran)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 14

Type: **Poster Presentation**

## Direct numerical simulation of two-phase fluid flow in two-dimensional porous media

The current research investigates the numerical simulation of incompressible two-phase flow of water and oil in a porous medium using the OpenFOAM software. The methodology for generating the porous geometry and grid study is explored. To facilitate a two-dimensional analysis, a single grid cell is constructed in the direction perpendicular to the planar domain. Subsequently, a water-oil mixture with an oil phase volume fraction of 0.5 is introduced from the left boundary of the computational domain. Owing to the imposed pressure gradient between the left and right boundaries, the multiphase fluid flow is driven towards the outlet, ultimately exiting through the right boundary. The numerical results demonstrate that a pressure differential of one pascal is maintained between the inlet and outlet flows. Additionally, due to the lower density of the oil phase relative to water, the oil phase exhibits a tendency to progressively stratify above the water phase within the porous medium.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** YOUSEFI, Soroush (School of Mechanical Engineering, Iran University of Science and Technology, 16846-13114, Tehran, Iran)

**Co-author:** POURFAROKH, Mohammad Reza (School of Mechanical Engineering, Iran University of Science and Technology, 16846-13114, Tehran, Iran)

**Presenter:** YOUSEFI, Soroush (School of Mechanical Engineering, Iran University of Science and Technology, 16846-13114, Tehran, Iran)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 15

Type: **Poster Presentation**

## **Comparison of the catalytic activity of a zirconium-based metal-organic framework and its defective structure in hydrogen production**

In this research, a zirconium-based metal-organic framework (MOF-801) and its post-synthetically produced modified structure (Quasi-801) were used to access unsaturated metal centers as active catalytic sites for hydrogen gas production using sodium borohydride ( $\text{NaBH}_4$ ). For this purpose, the zirconium-based metal-organic framework was first synthesized in dimethylformamide (DMF) solvent. Then, through controlled thermal treatment, the structure was modified, and the related quasi- metal-organic framework with unsaturated metal sites was created. The presence of these metal sites as Lewis acids in the catalytic reaction of hydrogen production from the hydrolysis of sodium borohydride proved to be effective and increased the catalytic efficiency. Additionally, the effects of temperature change on the catalytic activity of the metal-organic framework (and its modified structure) and the amount of hydrogen produced were investigated. An increase in reaction temperature activates some of the metal sites that are inactive at lower temperatures. Consequently, thermal modification added to the number of available sites for hydrogen production, two-fold increasing the process yield. According to the results, the thermal modification process effectively impacts the catalytic performance of the structure and improves the catalytic behavior of the structure. Therefore, the development of quasi- metal-organic frameworks can be an attractive method for developing hydrogen production catalysts as a clean fuel.

### **Student presentation contest**

Not Interested

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** ROUHANI, Farzaneh; ZEIRANI GASHTI, Maryam**Presenter:** ZEIRANI GASHTI, Maryam**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 16

Type: **Oral Presentation**

## Investigating the fluid behavior of the mixture of smoke and air in the porous filter part of the cigarette

*Wednesday, 25 September 2024 10:00 (15 minutes)*

Investigation of cigarette rod's fluid behavior and flow regime has a high importance regarding the concerns of human health and environmental perspectives. The simulation study in the case of cigarette smoke can be performed in time-dependent calculations for tobacco part and stationary calculations for the filter part. In this study, the modeling was tried to be accomplished in the filter part through COMSOL-Multiphysics software. Equations that were utilized for modeling contains the formulas of filter porosity and permeability in the fibrous beds. Employing the mentioned simulation tool, velocity and pressure contours, heat transfer behavior and some other elements can be obtained. By the comparison of the mentioned contours, the difference in the values of parameters such as velocity and pressure could be obviously observed (suction terminal to tobacco terminal).

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** HOSSEINI, Seyyed Reza (University of Tabriz, Department of Chemical Engineering and Petroleum)

**Co-authors:** Dr AGHDASINIA, Hassan (University of Tabriz, Department of Chemical Engineering and Petroleum); Prof. PEIGHAMBARDoust, Seyed Jamaledin (University of Tabriz, Department of Chemical Engineering and Petroleum)

**Presenter:** HOSSEINI, Seyyed Reza (University of Tabriz, Department of Chemical Engineering and Petroleum)

**Session Classification:** Parallel Session 7

**Track Classification:** Diverse Topics in Porous Media

Contribution ID: 17

Type: **Oral Presentation**

## Numerical Investigation of Spontaneous Imbibition of Power Law Fluids in Partially Saturated Porous Mediums

*Tuesday, 24 September 2024 09:45 (15 minutes)*

In this study, numerical investigation of Richard's equation of physiological liquids obeying power law rheological behavior has been investigated in partially double layered porous mediums based on effective viscosity concept. COMSOL Multiphysics has been selected to numerical solution of governing equations. Based on the obtained numerical results, the range of Reynolds number (which is defined based on averaged channel's inlet velocity) has always shown the values too smaller unity for different values of power law indexes which is an implicitly credential of validity of Darcy equation governed in porous mediums. Beside this, the results have shown the value of absorbed mass by the system has notably increased lower power law indexes (described as an improvement in the fluid's shear thinning behavior). Similarly, for a given power law fluid, increase on the thickness of the layer including larger permeability, leads to increase on the value of absorbed mass by the double layer porous mediums.

Keywords: Richard's Equation; Physiological Fluids; Power law model; Effective Viscosity; COM-SOL Software.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** Dr ASADI, hanieh (University of Tehran)

**Co-authors:** POURJAFAR, Mohammad (University of Tehran); Prof. SADEGHY, Kayvan (University of Tehran)

**Presenter:** Prof. SADEGHY, Kayvan (University of Tehran)

**Session Classification:** Parallel Session 3

**Track Classification:** Geotechnique/Soil Mechanics



Contribution ID: 18

Type: **Oral Presentation**

*Tuesday, 24 September 2024 10:00 (15 minutes)*

2019 年 12 月 31 日，本公司 2019 年度利润分配方案为：以 2019 年 12 月 31 日总股本 100,000,000 股为基数，向全体股东每 10 股派发现金股利 0.50 元（含税），共计派发现金股利 5,000,000.00 元。该方案已于 2020 年 3 月 10 日经 2019 年度股东大会审议通过，并于 2020 年 3 月 20 日实施完毕。

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Opt In

**Primary author:** JABBARZADEH, Milad

**Co-authors:** Mr VALIPOUR, Mehdi (Master of Science Student, Sharif University of Technology); Dr SADEGHI, Hamed (Associate Professor, Sharif University of Technology)

**Presenter:** JABBARZADEH, Milad

**Session Classification:** Parallel Session 3

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 20

Type: Oral Presentation

XX  
 XXX

Tuesday, 24 September 2024 10:00 (15 minutes)

XXXXXXXX

XX XXXXXXXX XXXXXXXX XXXXXXXXXXXXXXXX X XXXXXXXX XXXXX XXXXXXXXXXXXXXXX XXXXXXXXXXXX XX XXXXXXXX XXXX XXXXXXXXXXXX XXXXX  
 XXXXXXXX X XXXXXXXX XXXXX XXXXXXXXXXXXXXXX XXXXXXXXXXXX XXXXXXXX XXXXXXXXXXXXXXXX XXXXXXXX XXXXXXXX XXXX XXXXXXXX XXXXXXXX  
 XXXXXXXXXXXXXXXX XXXXXXXXXXXXXXX XX XXXXX XXXXXXXX XXXXXXXX XXXXXXXX XXXXXXXX X XXXXX XXXXXXXXXXXX XXXXXXXX XXXX XXXXXXXX  
 XXXXXXXXXXXXXXXX .XXX XX XXXX XXXXXXXX XX XXXXXXXXXXXX XXXXXXXX XX XXXXXXXXXXXX XXXXX XXXXXXXX XXXXX XXXXXXXX XXXXX XXXXXXXX  
 XXXXXXXX XXX XXXXXXXX XX XXXXX XXXXXXXXXXXXXXX XXXXXXXX XXXX XXXX XX XXXXXXXXXXXXXXX XXXXXXXX XXXXX XXXXXXXX  
 .XXX XX XXXX XXX XXXXXXX XXXX :XXX (1) XX XXXXXXXXXXXX XX XX XXXXX XXXXX X (2) XX XXXXXXXX XX XXXXX XXXXX  
 XXXXX XXXXXXX XXXXX XXXXXXXXXXXXXXX X XXXXXXXX XXXXXXXXXXXX XXXXXXXX XXXXXXX XXXXX XXXXXXXXXXXX XX XX XXXX XXXXXXX XXXXXXX  
 XXXXX X XXXXXXX .XXX XXXXXXX XXXXX XXXX XX XXXXXXXXXXX XXXXXXX XXXXX XX XXXXXXX XXXXXXX XXXXXXX XX XXXXXXX XX XXXXXXX  
 XXXXXXXXXXX XXXXXXX XXXXXXX XXXXXXX X XX XXXXXXXXXXX XXXXXXXXXXXX X XXXXXXX XXXXX XX XXXX XXXXXXX XXXXXXX XX XXX  
 XXXXX XXXXX .XXX

:XXX-XXXXXXXXXXXX XXXXXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXX XXXXXXX  
 XXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXXXXXXXXXX XXXXX XXXXXXXXXXXXXXX

#### 1. XXXXX

XXXXXXXX XXX XXXXXXXX XX XXXXXXX XXXXXXX XXXXXXXX XX XXXXXXX XXXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXX XXXXX XXXXX  
 XXX .XXX XXX XXXXXXX XX XXXXXXXX XX XXXXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXX X XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX  
 XXXXXXX XXXXXXX XXXXXXXX X XXXXXXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXX XX XXXXXXX .XXX XXX XX XXXXXXXX XXXXXXX  
 XX XXX XXXXXXXX XXXXXXX (segmentation) XXXXXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXXX .XXX XXX XXXXXXX XX  
 XXXXXXXX X XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX  
 XXXXXXX XXXXX XXXXXXXXXXXXXXX XXXXXXX XXXX ]12[.

XXXXXXXX XXXXXXXX XX XXXXX XXXXXXX XXXXX XXXXXXX XXXXXXX XX XXXXXXX XXXXXXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXX  
 XX XXXXXXX XXXXXXX XXXXXXX .XXX XXX XXXXXXX XXXXX XXXXXXX XXXXX XXXXXXX XXXX XXXXXXXXXXXXXXX XXXXXXXX XX  
 XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXX XXXXXXX X XX XXXXX XXXXXXX XXXXXXX XXXXXXX .XXX XXX XXXXXXX XXXXXXXX  
 XXXXXXXXXXXXXXX XX XXXXXXX XXXXXXXXXXXXXXX XXXXX XX XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX XX XXXXXXXXXXXXXXX XXXXX X XXXXX XXXXXXXX  
 XXXXXXXX XXXXX X XXXXXXX XXXXXXX XX XXXX X XXXXXXX XXXXXXXX XXXXX XX XXXX XXXXXXX XXXXX XXXXX ]2-4[.

XX XXXXXXX XXXXXXX XXXXXXXX XX XXXXXXXXXXX XXXXX X XXXXXXX XXXXXXXX XXXXX XXXXXXXXXXXXXXX (CNN) ]2[ XXXX  
 XXXXXXX XX XXXXXXX XXXXXXX XXXXXXXXXXX XXXXXXX XXXXX .XXX XXX XXXXXXX XX XXXXX XXXXXXXXXXX XXXXXXX XXXX  
 XXXXXXXXXXX XXXXXXXX X XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX XXX XXXXXXX XXXXXXXXXXX XXXXXXX XXXXXXX XXXXXXX  
 XXXXXXX XXXXXXXX .XXX XXX XX XXXXXXX XXX XXXXXXXXXXX XXXXXXX XXXXXXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX  
 XX XXXXX XXXXXXXXXXXXXXX XXXXXXXXXXX XXXX XXXX ]23[. XXX XXXXX XXX XXXXXXXXXXX XXXXXXX XXXXXXXXXXX XXXXXXXXXXXXXXX  
 X XXXXXXX XX XXXX XXXXXXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX .XXX

#### 2. XXX XXX

XX XXX XXXXXXX XXXXXXX XXXXXXXX XX XXXXXXXXXXX XXXXXXX XXXXX XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX .XXX XXX  
 XXX XXX XXXXXXX XXXX :XXX XXX XXXXX XX XXXXX XXXXX XX XXXXXXX XXXXXXX XXXXX XXXXXXXXXXXXXXX X XXXXXXX XX  
 XXXXXXX XXXXXXX XXXX) X((XXX)1 X XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXXXXXXXXXX X XXXXXXX  
 XXX XXXXXXX XXXXXXXXXXX XXX XXXXXXX XXXXXXX XXXX) .((X)1 XXX XXX XXXXXXX XXX XX XXX XXXXXXX XXXXXXX  
 XXXXXXX XXXXXXX XXXXXXXXXXXXXXX XXXXX XXX XXXXXXX XXX XXXXX XXX XXXXXXX XXXXXXX (MDSR) ]5[ XXX XX XX  
 XXX XXX XXXXXXX XXXXXXX XXX XXXXXXXXXXX XXXXX XXXXXXX XXXXXXXXXXXXXXX XX XXXXXXXXXXX XXX XXXXX CNN XX XX  
 XXXXXXX ResNet XXXXX XXXXXXX XXXXXXXXXXX XXX XXXX X XXXXX XXX XXXXXXX XXX XXXXXXX XXXX Unet3+ XXXXXXX ]4[.  
 XXXXXXXXXXX XXXXXXXXXXXXXXX XX XXXXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX ]6[ XXXX) 2) XXXXX XXXXXXX X XXXXXXXXXXX XXX XXXXXXX  
 XXXXXXXXXXX .XX XXXXXXXXXXX XXXXXXXXXXX XXXXX XXX XXXXXXX XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX X XXXXXXXXXXXXXXX  
 XXXXX XXXXXXXXXXXXXXX .XXX XXX XXX XXXXXXXXXXX XXXXXXX XXXXXXX XXXXXXX XXX XXXXXXX XXX XXXXXXX XXX XXXXXXX  
 XXXXXXX XXXXX X XXX XXXXXXX XXXXX XXXXXXXXXXX XXXXXXX XXXXX XXXXX ]6[.

1. XXXXXXXXXXX XXX XXX XXXXXXX XXXXX XXXXXXXXXXX XXX XXXXXXXXXXX XXXXXXXXXXXXXXX XXXXXXX XX XX XXXXXXXX  
 XXX XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX XXXXX XXXXXXXXXXX XXX XXXXXXX XXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXX X XXXXX XX  
 XXXXX XX XXXXX X XXXXX XXXXXXX XXXX X XXX XXXXXXX XX XXXXX XX XXXXX XXXXXXX .XXX XXXXXXXXXXX

در این مقاله، روشی برای استخراج و طبقه‌بندی خودکار اجزای مختلف سنگ (مانند ماتریکس، ماکروپوئز و میکروپوئز) از تصاویر سه‌بعدی (3D) به دست آمده از دستگاه آویزو (Avizo) ارائه شده است. این روش بر اساس شبکه‌های عصبی عمیق (Deep Learning) و به‌ویژه مدل‌های مبتنی بر یونیفای (U-Net) طراحی شده است. نتایج حاصل از این روش با نتایج دستی (Hand-drawn) مقایسه شده و دقت بسیار بالایی در استخراج و طبقه‌بندی اجزای مختلف سنگ به دست آمده است. همچنین، این روش قادر است به‌طور خودکار و بدون نیاز به دخالت انسان، اجزای مختلف سنگ را از یک تصویر سه‌بعدی استخراج و طبقه‌بندی کند. این روش می‌تواند به‌طور گسترده در زمینه‌های مختلف زمین‌شناسی و مهندسی نفت به کار رود.

تابلو 1. مقایسه نتایج استخراج اجزای مختلف سنگ از تصاویر سه‌بعدی به دست آمده از دستگاه آویزو (Avizo) با نتایج دستی (Hand-drawn).

مقاله شماره 1

(macroporosity) استخراج و طبقه‌بندی

(microporosity) استخراج و طبقه‌بندی

HR-Watershed 1781/0 (0.00%) 1266/0 (0.00%) 6953/0 (0.00%) 0433/0 (0.00%) 1065/0 (0.00%) 1287/0 (0.00%) 15833-

(0.00%)  
EDSR-UResNet 1881/0 (61/5 %) 1413/0 (61/11 %) 6706/0 (12/1- %) 0375/0 (4/13- %) 0803/0 (6/24- %)  
0867/0 (6/32- %) 11278-

(7/28 %)  
dBMDSR-UNet3Plus 1802/0 (18/1 %) 1289/0 (82/1 %) 6909/0 (23/2- %) 0369/0 (8/14- %) 0777/0 (1/27- %)  
0777/0 (6/39- %) 10673-

(6/32 %)

تابلو 2. مقایسه نتایج استخراج اجزای مختلف سنگ از تصاویر سه‌بعدی به دست آمده از دستگاه آویزو (Avizo) با نتایج دستی (Hand-drawn).

مقاله شماره 2

(macroporosity) استخراج و طبقه‌بندی

(microporosity) استخراج و طبقه‌بندی

HR-Watershed 1058

(0.00%) 1359

(0.00%)

EDSR-UResNet 1424

(61/34 %) 1526

(32/12 %)

dBMDSR-UNet3Plus 1140

(74/7 %) 1252

(78/7- %)

4.

[1] Song, W., Liu, L., Wang, W., & Jiang, X. (2021). Deep Learning Techniques for Digital Rock Physics and Its Applications in the Petroleum Industry: A Review. *Journal of Petroleum Science and Engineering*, 196, 107830.

[2] Ranneberger, O., Fischer, P., & Brox, T. (2015). U-Net: Convolutional Networks for Biomedical Image Segmentation. In *International Conference on Medical Image Computing and Computer-Assisted Intervention (MICCAI)* (pp. 234-241).

[3] Pham, C. H., Ducournau, A., Fablet, R., & Rousseau, F. (2018). Brain MRI Super-Resolution Using Deep 3D Convolutional Networks. In *2018 IEEE 15th International Symposium on Biomedical Imaging (ISBI 2018)* (pp. 197-200).

- [4] Huang, H., Lin, L., Tong, R., Hu, H., Zhang, Q., Iwamoto, Y., ... & Chen, Y. W. (2020). UNet 3+: A Full-Scale Connected UNet for Medical Image Segmentation. In ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (pp. 1055-1059). IEEE.
- [5] Lim, B., Son, S., Kim, H., Nah, S., & Lee, K. M. (2017). Enhanced Deep Residual Networks for Single Image Super-Resolution. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPRW) (pp. 136-144).
- [6] Alqahtani, N. J., Niu, Y., Wang, Y. D., Chung, T., Lanetc, Z., Zhuravljov, A., & Mostaghimi, P. (2022). Super-resolved segmentation of X-ray images of carbonate rocks using deep learning. Transport in Porous Media, 143(2), 497-525.

### **Student presentation contest**

Not Interested

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** BAKHTIARY, Mohammad

**Co-author:** QAJAR, Jafar (Department of Petroleum Engineering, Shiraz University)

**Presenter:** BAKHTIARY, Mohammad

**Session Classification:** Parallel Session 4

**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 21

Type: **Oral Presentation**

## Controlling Factors of Porosity and Reservoir Quality in Carbonate Reservoirs

*Wednesday, 25 September 2024 09:45 (15 minutes)*

In terms of geology and reservoir characteristics, carbonate reservoir rocks are very complex and heterogeneous due to the influence of diagenetic processes. This article studies the Fahliyan Formation oil reservoir in one of the largest hydrocarbon fields in southwestern Iran. Based on core data and petrophysical logs from two wells, the factors controlling the development of porosity and reservoir heterogeneity in this field have been examined. The study results indicate that the reservoir heterogeneity in this field is not inherited from the depositional environment and its prevailing conditions, but diagenetic processes have played a more prominent role. Most of the primary pores have been lost through diagenetic processes such as cementation and compaction, and the reservoir has a higher abundance of pores smaller than 4 microns (mesopores and micropores). Additionally, the integration of core data, XRD, and petrophysical logs shows that due to dolomitization in the middle parts of the reservoir rock, fractures have been created and developed, which is an important factor in oil production in the field.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** ESRAFILI-DIZAJI, Behrooz (Assistant Professor, Department of Petroleum Exploration at University of Tehran); Mrs IMANI, Roghayeh (Student)

**Presenter:** Mrs IMANI, Roghayeh (Student)

**Session Classification:** Parallel Session 7

**Track Classification:** Diverse Topics in Porous Media

Contribution ID: 22

Type: **Oral Presentation**

## **Investigating the impact of slope angle on the effectiveness of the slit barriers in dissipating the kinetic energy of debris flows**

*Tuesday, 24 September 2024 10:15 (15 minutes)*

Debris flows are comprised of water and loose sedimentary deposits that occur in mountainous regions as a result of intense precipitation. Due to the rapid speed and massive volume of these flows, rigid barriers are installed along the flow path to dissipate the energy of the flow and prevent damage to downstream infrastructures. Nevertheless, the efficiency of these barriers is significantly affected by the velocity of the flow. Ignoring the approach velocity may even contribute to an increase in the energy and destructive power of the flow downstream. Hence, in this study, the influence of the slope angle of the bed, which is a crucial determinant of flow velocity, on the effectiveness of the barriers is investigated. According to findings from the FLOW-3D software, the installation of a row of cubic barriers on steep slopes leads to an increase in flow kinetic energy. However, barriers have no impact on energy dissipation on moderate slopes. In contrast, the construction of cubic barriers lowers the flow kinetic energy by more than 50% on moderate slopes.

### **Keywords**

Debris flow, Rigid barriers, Slit barriers, Energy dissipator, FLOW-3D

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Not Interested

**Primary author:** Ms AGHAGOLI, Anahita (M.Sc. Student, Department of Civil Engineering, Sharif University of Technology, Tehran, Iran.)

**Co-author:** Dr SADEGHI, Hamed (Associate Professor, Department of Civil Engineering, Sharif University of Technology, Tehran, Iran.)

**Presenter:** Ms AGHAGOLI, Anahita (M.Sc. Student, Department of Civil Engineering, Sharif University of Technology, Tehran, Iran.)

**Session Classification:** Parallel Session 3

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 23

Type: **Poster Presentation**

## Comparative Analysis of Porous Organic and Inorganic Materials for Drug Delivery

This review examines the properties and applications of porous organic and inorganic materials in drug delivery systems. Porous organic materials, such as Poly(D,L-lactide-co-glycolide), (PLGA) and chitosan, are valuable due to their biocompatibility and biodegradability, and they are suitable for integration with biological tissues. In contrast, porous minerals such as silica and alumina offer superior thermal and chemical stability, ideal for demanding medical environments such as cancer treatment. This comparative analysis addresses their synthesis, functionalization, and specific applications and highlights the necessity of selecting materials based on therapeutic needs and drug delivery requirements. This review emphasizes the ongoing developments that increase the effectiveness of these materials in medical applications focusing on the pore properties of the compounds.

### Student presentation contest

Not Interested

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** AHADI-JOMAIRAN, Navid (PhD Student in Chemical Engineering, Department of Chemical Engineering, University of Mohaghegh Ardabili, Ardabil, Iran.); Prof. NEMATOLLAHZADEH, Ali (Professor, Chemical Engineering, Department of Chemical Engineering, University of Mohaghegh Ardabili, Ardabil, Iran.)

**Presenter:** AHADI-JOMAIRAN, Navid (PhD Student in Chemical Engineering, Department of Chemical Engineering, University of Mohaghegh Ardabili, Ardabil, Iran.)

**Track Classification:** New Energies / Underground Gas Storage

Contribution ID: 24

Type: **Oral Presentation**

## **Effect of Salinity on Foam Flow Behavior for Conformance Control in Gas-Based Injection Processes: A Micro-scale Study**

*Tuesday, 24 September 2024 10:15 (15 minutes)*

Foam injection is an effective technique for enhancing the performance of gas-based processes in porous media. However, brine salinity is one of the factors that can significantly impact foam performance for subsurface applications. This study investigates the flow performance of foam generated using sodium dodecyl sulfate (SDS) as a foaming agent in two brine salinity levels (5000 and 35000 ppm NaCl) within a heterogeneous layered porous medium. A glass micromodel consisting of two layers with different permeabilities and fluid connectivity was used to conduct the experiments. The results revealed that the foam formed under low salinity conditions exhibited smaller bubbles, leading to increased apparent viscosity and consequently better control of gas phase mobility in both layers. The formation of a stable foam effectively controlled gas flow conformance in the high-permeability layer, resulting in the foam front advancing through both low-permeability and high-permeability layers. In contrast, under high salinity conditions, foam bubbles were larger and less stable, leading to faster gas phase breakthrough in the high-permeability layer and consequently reducing the effectiveness of foam injection for conformance control. The findings of this study demonstrate the superior performance of foam under low salinity conditions for conformance control in gas injection processes in a heterogeneous layered system. This can lead to improved sweep efficiency of the injected gas in the porous medium.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** Mr MOLAEI, Amir Hossein; Dr SIMJOO, Mohammad; Mr SHAHIN, Matin**Presenter:** Mr SHAHIN, Matin**Session Classification:** Parallel Session 2**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media



Contribution ID: 25

Type: **Oral Presentation**

## **Improving the challenge of imaging resolution and field of view in permeability estimation by integrating multiscale imaging of carbonate rocks and Deep Learning**

Digital rock physics, as a pioneering technology in characterizing porous structures by integrating state of the art tomographic imaging and advanced numerical simulations, extracts key rock properties such as permeability. However, limitations in imaging resolution and field of view (FOV) at the pore scale pose significant challenges. Direct numerical simulations at larger scales are either computationally impractical or prohibitively expensive. This trade-off between FOV and image resolution is particularly evident in the complex and multiscale pore structures of carbonate rocks. To address this issue, a novel machine learning approach has been developed to integrate multiscale imaging data of various resolutions. This method uniquely employs an optimized three-dimensional convolutional neural network (CNN) model to identify intricate cross-scale correlations, facilitating accurate predictions of transport properties at larger scales beyond the reach of traditional direct simulation techniques. Additionally, by utilizing a cross-scale transfer learning method during the training phase, the developed model achieves robust performance with an  $R^2$  exceeding 0.96 when evaluated on lower-resolution domains with larger FOVs. The proposed workflow, initially designed for the complex porous media of carbonate rocks, demonstrates adaptability to various multiscale porous materials, thereby offering a promising solution to the inherent limitation of the trade-off between imaging resolution and FOV in digital rock physics.

Keywords: Digital Rock Physics; Multiscale Tomographic Imaging; Carbonate Reservoirs; Deep Learning; Transfer Learning

### **Student presentation contest**

Not Interested

### **Journal Submission**

Not Interested

### **Student Poster Contest**

Opt In

**Primary author:** NABIPOUR, Iman (PhD candidate)

**Co-authors:** QAJAR, Jafar (Department of Petroleum Engineering, Shiraz University); Dr MOHAMMADZADE, Meisam

**Presenter:** NABIPOUR, Iman (PhD candidate)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 26

Type: **Oral Presentation**

## **Geothermal recovery of abandoned oil wells: The effect of insulation on the efficiency of coaxial borehole heat exchangers**

*Wednesday, 25 September 2024 09:45 (15 minutes)*

Using abandoned oil and gas wells as coaxial borehole heat exchangers paves the way for reusing these wells for geothermal energy extraction and low-carbon electricity generation. In this study, 150 different scenarios of such energy extraction processes have been modelled to examine the impact of inner tube's insulation on the output energy. It is shown that, on average, the performance coefficient of the exchanger is 3 times higher with the use of effective insulation. The results of this research lead to more effective use of abandoned wells and increased economic and energy efficiency of these systems.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** Mr AHMADPOOR, Yasin (Institute of Petroleum Engineering, School of Chemical Engineering, College of Engineering, University of Tehran); Dr SAJJADI, Mozhdeh (Assistant Professor); Dr EMAMI NIRI, Mohammad (Institute of Petroleum Engineering, School of Chemical Engineering, College of Engineering, University of Tehran)

**Presenters:** Mr AHMADPOOR, Yasin (Institute of Petroleum Engineering, School of Chemical Engineering, College of Engineering, University of Tehran); Dr SAJJADI, Mozhdeh (Assistant Professor)

**Session Classification:** Parallel Session 6

**Track Classification:** New Energies / Underground Gas Storage

Contribution ID: 27

Type: **Poster Presentation**

## **Simultaneous investigation of the effect of Rock morphology and capillary number on water breakthrough time**

The current study focuses on pore-scale simulation and analysis of oil displacement in digital rocks, a novel approach for tracking and enhancing oil recovery in porous media. This research explores the impact of water flooding on oil recovery in three digital rock samples with identical porosity but varying morphologies. Utilizing computational fluid dynamics, numerical simulations were conducted to assess the influence of pore and throat sizes on water breakthrough time, residual oil saturation, and oil displacement patterns. Injection speed, mobility ratio, and interfacial tension were manipulated to investigate these effects further. The findings reveal that rocks with smaller pores and throats facilitate faster water breakthrough and reduced breakthrough time. Conversely, enlarging these features leads to increased fingering time. The morphology of the rock significantly influences the oil recovery process, influencing the fingering regime based on breakthrough time and pore injection.

### **Student presentation contest**

Opt in

### **Journal Submission**

Not Interested

### **Student Poster Contest**

Opt In

**Primary author:** Mr GHODSI, Mohammad (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Co-author:** Dr RASAEI, Mohammad Reza (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Presenter:** Mr GHODSI, Mohammad (Institute of Petroleum Engineering, School of Chemical Engineering, Faculty of Engineering, University of Tehran)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 28

Type: **Oral Presentation**

## Investigating the Effects of Porous Media on the Minimum Miscibility Pressure of an Asphaltenic Oil Sample and Gas

*Tuesday, 24 September 2024 10:15 (15 minutes)*

Gas injection into oil reservoirs encounters several challenges, including the presence of nanopores, asphaltene precipitation, and adsorption of fluid molecules on the porous medium. Miscible gas injection has been shown to be the most efficient method in many cases. Therefore, estimating the minimum miscibility pressure (MMP) is crucial in this process. However, the presence of fluid in the porous medium significantly affects its phase behavior, leading to differences in parameters such as MMP compared to the bulk phase. This study investigates the simultaneous effects of confinement (shift in critical properties of components, adsorption of fluid molecules on the porous medium, and capillary pressure) and asphaltene precipitation on the miscibility of an asphaltenic oil sample with CO<sub>2</sub> and NGL gases using modified Peng-Robinson (PR) and cubic-plus-association (CPA) equations of state. The results indicated that asphaltene precipitation significantly delays the miscibility process, with this phenomenon occurring more intensely for CO<sub>2</sub>. Additionally, the effects of the porous medium on MMP are not negligible at radii less than 100 nm, while at radii greater than this value, the phase behavior approaches the bulk phase.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** Dr SAFAEI, Ali (Fouman Faculty of Engineering, College of Engineering, University of Tehran, Tehran, Iran, Enhanced Oil Recovery (EOR) Research Centre, IOR/EOR Research Institute, Shiraz University, Shiraz, Iran); Dr QAJAR, Jafar (Department of Petroleum Engineering, School of Chemical and Petroleum Engineering, Shiraz University, Shiraz, Iran, Department of Earth Sciences, Faculty of Geosciences, Utrecht University, Utrecht, The Netherlands); Prof. RIAZI, Masoud (Enhanced Oil Recovery (EOR) Research Centre, IOR/EOR Research Institute, Shiraz University, Shiraz, Iran, School of Mining and Geoscience, Nazarbayev University, Astana, Kazakhstan); Dr KAZEMZADEH, Yousef (Department of Petroleum Engineering, Faculty of Petroleum, Gas, and Petrochemical Engineering, Persian Gulf University, Bushehr, Iran)

**Co-author:** KEYVANI, Fatemeh (Department of Petroleum Engineering, School of Chemical and Petroleum Engineering, Shiraz University, Shiraz, Iran)

**Presenter:** KEYVANI, Fatemeh (Department of Petroleum Engineering, School of Chemical and Petroleum Engineering, Shiraz University, Shiraz, Iran)

**Session Classification:** Parallel Session 1

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 29

Type: **Oral Presentation**

## Effect of time constant and rock pore complexity on the shift factor for non-Newtonian fluid flow in porous media

*Tuesday, 24 September 2024 10:30 (15 minutes)*

Non-Newtonian fluid flow within porous media, exemplified by polymer remediation of contaminated groundwater/aquifer systems, presents complex challenges due to the fluids' complex rheological behavior within 3D tortuous pore structures. This paper introduces a pore-scale flow simulator based on the OpenFOAM open-source library, designed to model shear-thinning flow within porous media. Leveraging this developed solver, extensive pore-scale flow simulations were conducted on  $\mu$ -CT images of various real porous media with varying complexity for Cross-fluid model. We focused on the macroscale-averaged deviation between bulk viscosity and the in-situ viscosity, commonly denoted by a shift factor. We provided an in-depth evaluation of the shift factor's dependency on the time constant and the rock's pore space complexity. The effect of time constant on shift factor is very small. Also demonstrate how the shift factor fluctuates based on tortuosity, characteristic pore length, and the cementation exponent. In particular, less porous/permeable systems with smaller characteristic pore lengths exhibited larger shift factors due to higher variations of shear rate and local viscosity in narrower flow paths. Additionally, the shift factor increased as rock became more tortuous and heterogeneous.

### Student presentation contest

Not Interested

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** AMIRI, Mehdi; QAJAR, Jafar (Department of Petroleum Engineering, Shiraz University); QASEMINEJAD RAEINI, Ali (Research Associate)

**Presenter:** AMIRI, Mehdi

**Session Classification:** Parallel Session 1

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 30

Type: **Oral Presentation**

XXXXXXXXXX XXXXXX XXXXXXXXXXXXX X XXXXXXXXXXX XXXXXXXXXXXX XXXX XXX XXXXXXXXXXX  
 XXXXXXXXXXX XXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXX XXXXXXX XXXX  
 XXXXXXXXXXXXXXXXXXXX XXXX XXXX X XXXX XXX XXXXXXX XXX XXXXXXXXXXX XXXX

*Tuesday, 24 September 2024 10:30 (15 minutes)*

XXXXXXXXXXXXXXXX XXX XXX XXXX XXX XXX-XXXXXXXX XXX XXX XXXXXXXXXXX XXX XXX XXXXXXXXXXX XXX-XXX XXX XXXXXXX  
 XXXXXXXXXXX XXXXXX XXXX XXXXXXXXXXX XXXXXXX XXXXXXXXXXX X XXXXXXX XXXXXXXXXXX XXX XXXX XXXXXXXXXXX XXXX XXX  
 XXXXXXX XXXX-XXX X XXXXXXXXXXX XXX XXXXXXX XXX XXXXXXXXXXXXXXXXXXX XXXXXXX XXX XXX XXXXXXXXXXX XXXX-XXX X XXX-XXXX  
 XXX XXX XXX XXXXXXX XXXXXXX XXXXXXX-XXX XXX XXXXXXX XXX XXXXXXXXXXX XXX XXXXXXXXXXX XXXX XXX XXXX XXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXX XXXXXXX XXX XXX XXXX XXXXXXX XXX XXXXXXX XXX XXXXXXX XXXXXXX XXXXXXX XXXX (SCM) X XXXXXXX  
 XXXXXXX XXXXXXX XXX XXXXXXXXXXX XXX XXXXXXXXXXX XXX XXX XXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXX XXXXXXX XXX  
 XXX XXX .XXXX XXX XXX XXXX XXXXXXX XXXXXXXXXXX XXX XXX XXX XXXXXXX XXX XXXXXXXXXXX XXXX-XXXX (θ) XXXX  
 XXXXXXXXXXXXXXXXXXX XXXXXXX XXXX X XXXX XXXXXXXXXXX XXXXXXX XXX XXXXXXX XXX XXXX XXX XXXXXXX XXXXXXXXXXX XXXXXXX  
 XXXXXXX .XXXX-XXX XXX XXX XXX XXXX XXXXXXX XXXXXXX XXXX XXXX XXX XXXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXX  
 XXXX XXXXXXX XXXX XXXX .XXXX XXXXXXX XXX XXXXXXX XXXX XXXX-XXX XXX XXXX XXXX XXX XXX XXXX XXXXXXX XXX  
 XXXXXXX X XXXXXXX XXX XXXX XXX XXXXXXX XXXXXXX-XXX XXX XXX XXXXXXX pH XXXX XXX XXXX XXX pH > 8 X XXXX  
 XXX XXXX XXX XXX XXXXXXX XXXX XXXXXXX-XXX XXXX XXX XXXXXXX XXXXXXXXXXX XXXX XXX XXXXXXX XXXXXXX XXX XXXXXXX  
 XXXX .XXXX XXX XXXXXXX XXXX XXXX XXX XXX XXXX XXXXXXX XXXX) XXXX (XXX XXX XXX XXXXXXX-XXX XXXXXXX  
 XXXXXXXXXXX XXXXXXX XXX XXXXXXX XXXX-XXX XXX XXX XXXXXXX XXXX XXXXXXX XXXXXXX XXXX XXX XXX XXXX .XXXX XXX  
 XXX XXXXXXXXXXX XXX XXXX XXXX XXXXXXX XXX XXXXXXX XXXX XXX XXXXXXX XXX .XXXX

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Opt In

**Primary authors:** Mr ALMASIYAN, Pouriya (Sharif University of Technology); Prof. MAHANI, Hassan (Sharif University of Technology)

**Presenters:** Mr ALMASIYAN, Pouriya (Sharif University of Technology); Prof. MAHANI, Hassan (Sharif University of Technology)

**Session Classification:** Parallel Session 2

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 31

Type: Oral Presentation

## Benchmarking the potential of Super-Resolution Convolutional Neural Networks in Improving the Resolution of Digital Rock Images

*Tuesday, 24 September 2024 10:30 (15 minutes)*

### Abstract

The ultimate objective of digital rock physics is to accurately predict rock properties. However, the resolution of rock images obtained from imaging techniques often involves a trade-off between image resolution and field of view (FoV) (Bai, Berezovsky et al. 2020, Sadeghnejad, Enzmann et al. 2021). The presence of heterogeneous rocks presents a significant challenge in accurate modeling due to the need to capture information at various scales. Various multi-scale modeling approaches have been employed to address this issue. In response, alternative methods have been explored to reconstruct rock images using advanced artificial intelligence algorithms, such as artificial neural networks. These state-of-the-art methods offer improved connectivity features in final images, reduced computational costs, and the ability to incorporate large-scale heterogeneities into reconstructed structures (Da Wang, Armstrong et al. 2019). However, it is crucial to recognize the challenges associated with these approaches. Super-resolution (SR) methods have emerged as a prominent solution to enhance resolution (Da Wang, Shabaninejad et al. 2021). Super resolution (SR) is an eminent system in the field of computer vision and image processing to improve the visual perception of the poor-quality images (Lepcha, Dawa Chyophel, et al. 2023).

This research aims to evaluate the speed and accuracy of deep learning methods, specifically the SR-Convolutional Neural Network (SRCNN), its modified counterpart, and the Fast-SRCNN (FSRCNN). The dataset for model evaluation consisted of a Berea sandstone sample that was scanned at the DESY PETRA-III X-ray synchrotron light source in Hamburg, Germany. In this study, an SRCNN architecture underwent two significant modifications (referred to as transient architectures) to transform into an FSRCNN architecture. Firstly, an additional deconvolution layer was integrated into the last layer of the network, enabling direct mapping between input and output images and eliminating the need for pre-processing on Low-Resolution (LR) images. Secondly, a mapping layer was formulated to compress and expand input features to enhance the mapping process. Lastly, smaller-sized filters with additional mapping layers were employed.

The results demonstrate that the FSRCNN surpasses the SRCNN and all transient architectures in terms of speed and resolution enhancement, achieving a significant improvement of over 20 times. Additionally, the petrophysical properties of super-resolved images generated by FSRCNN, SRCNN, and the modified architectures, as well as the HR images, were calculated. The porosity and permeability of the digital twins reconstructed by the FSRCNN exhibit similar values to HR images, underscoring the superiority of the FSRCNN approach in accurately capturing the intricate details of digital rocks and enhancing the reliability of subsequent petrophysical analysis.

**Keywords:** Digital Rock Physics; Super Resolution; Convolutional Neural Network; Petrophysical Analysis; Accuracy, Speed

### References

- Bai, Y., V. Berezovsky and V. Popov (2020). Super Resolution for Digital Rock Core Images via FSRCNN. Proceedings of the 2020 4th High Performance Computing and Cluster Technologies Conference & 2020 3rd International Conference on Big Data and Artificial Intelligence.
- Da Wang, Y., R. T. Armstrong and P. Mostaghimi (2019). "Enhancing resolution of digital rock images with super resolution convolutional neural networks." *Journal of Petroleum Science and Engineering* 182: 106261.
- Da Wang, Y., M. Shabaninejad, R. T. Armstrong and P. Mostaghimi (2021). "Deep neural networks for improving physical accuracy of 2D and 3D multi-mineral segmentation of rock micro-CT im-



ages." Applied Soft Computing 104: 107185.

Sadeghnejad, S., F. Enzmann and M. Kersten (2021). "Digital rock physics, chemistry, and biology: challenges and prospects of pore-scale modelling approach." Applied Geochemistry 131: 105028.

Lepcha, Dawa Chyophel, et al. "Image super-resolution: A comprehensive review, recent trends, challenges and applications." Information Fusion 91 (2023): 230-260.

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Opt In

**Primary authors:** SADEGHI, Pouya (Tarbiat Modares University); Dr SADEGHNEJAD, Saeid (1. Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran 2. Johannes Gutenberg-University Mainz, Germany)

**Co-authors:** Mr MOSLEMIPOOR, Abolfazl (1. Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran 2. Johannes Gutenberg-University Mainz, Germany); ENZMANN, Frieder; KERSTEN, Michael (Johannes Gutenberg-University Mainz, Germany)

**Presenter:** Dr SADEGHNEJAD, Saeid (1. Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran 2. Johannes Gutenberg-University Mainz, Germany)

**Session Classification:** Parallel Session 4

**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 32

Type: **Oral Presentation**




Wednesday, 25 September 2024 10:30 (15 minutes)

[illegible][illegible]

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 104

1. 

1. **Введение**  
 В настоящее время одним из наиболее актуальных направлений в области информатики является разработка интеллектуальных систем, способных выполнять задачи, требующие творческого подхода и принятия решений. Такие системы находят широкое применение в различных областях, включая медицину, образование, бизнес и науку. В данной работе рассматриваются методы и алгоритмы, позволяющие создавать интеллектуальные системы, способные решать задачи, связанные с анализом данных, классификацией объектов и прогнозированием.

1: 





[illegible]

2. 

Figure 8 shows the results of the 80 and 240 MHz experiments. The 80 MHz experiment shows a clear peak at 0.5 ppm, which is assigned to the  $\alpha$ -methyl group of the polymer. The 240 MHz experiment shows a clear peak at 0.5 ppm, which is assigned to the  $\alpha$ -methyl group of the polymer. The results of the 80 and 240 MHz experiments are consistent with the results of the 100 MHz experiment.

[illegible]

走廊 (corridors) 是连接不同区域的关键通道。在本文中，我们使用走廊来描述网络中的连接。走廊的宽度表示连接的数量。走廊的宽度越大，连接的数量越多。走廊的宽度越小，连接的数量越少。走廊的宽度为 4 表示连接的数量为 4。走廊的宽度为 1000 表示连接的数量为 1000。走廊的宽度为 Super K 表示连接的数量为 Super K [7]。走廊的宽度为 4 表示连接的数量为 4。走廊的宽度为 1000 表示连接的数量为 1000。走廊的宽度为 Super K 表示连接的数量为 Super K。走廊的宽度为 4 表示连接的数量为 4。走廊的宽度为 1000 表示连接的数量为 1000。走廊的宽度为 Super K 表示连接的数量为 Super K。

2: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039

Figure 3:  A 2D grid of 10x10 squares, each containing a small crosshair. This represents a discretized spatial domain.

[illegible]

1. 

[1]

J. Warren, "Dolomite: occurrence, evolution and economically important association", *Earth-Science Reviews* 52-2000. 1-81, July 2000.

[2] V. Tavakoli, "Permeability's response to dolomitization, clues from Permian–Triassic reservoirs of the central Persian Gulf", *Marine and Petroleum Geology* 123(2), DOI: 10.1016/j.marpetgeo.2020.104723, Jan 2021.

[3] V. Tavakoli, A. Jamaljan “Porosity evolution in dolomitized Permian–Triassic strata of the Persian Gulf, insights into the porosity origin of dolomite reservoirs”, *Journal of Petroleum Science and Engineering* 181(4):106191 DOI: 10.1016/j.petrol.2019.106191, Jun 2019.

[4] H. Rahimpour-Bonab, B. Esrafil-Dizaji, V. Tavakoli, "Dolomitization and anhydrite precipitation in permo-triassic carbonates at the south pars gasfield, offshore Iran: controls on reservoir quality", *Journal of Petroleum Geology*, Vol. 33(2), pp 1 - 24, January 2010.

[5] B. Esrafil-Dizaji, H. Rahimpour-Bonab, "Effects of depositional and diagenetic characteristics on carbonate reservoir quality: a case study from the South Pars gas field in the Persian Gulf", *Petroleum Geoscience*, Vol. 15 2009, pp. 325–344, DOI:10.1144/1354-079309-817, February 2009.

[6] M. Hosseinzadeh, V. Tavakoli, "The Effect of Geological Parameters on the Ratio of Horizontal to Vertical Permeability in Carbonate Reservoirs of Kangan and Upper Dalan Formations", *Petroleum Research*, Vol. 32, No. 123, 15-16 DOI:10.22078/pr.2022.4465.3020, (June-July) 2022.

[7] F. Gisquet, M. Floquet, B. Caline, A. Virgone, J. Borgomano, “Dolomite Outcrop Analogues as a Key to Understand the Development of Super-K Layers in a Giant Carbonate Reservoir (Upper Khuff Formation, Middle-East)”, ICE Cancun 2016, Mexico, Gisquet et al. September 2016.

### **Student presentation contest**

Not Interested

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Not Interested

**Primary author:** Mr NADERI, Mehrangiz (POGC)

**Co-author:** Mr AZIMVAND, Ali (POGC)

**Presenter:** Mr NADERI, Mehrangiz (POGC)

**Session Classification:** Parallel Session 5

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 33

Type: **Oral Presentation**

*Tuesday, 24 September 2024 10:15 (15 minutes)*

在本文中，我们使用 ImageJ 和 MATLAB 对 PoreFoam 模型进行了后处理。首先，我们使用 ImageJ 对模型进行了二值化处理，并计算了模型的孔隙率。然后，我们使用 MATLAB 对模型进行了三维重建，并计算了模型的表面积和体积。最后，我们使用 MATLAB 对模型进行了可视化，并生成了模型的 3D 渲染图。

## Student presentation contest

Opt in

## Journal Submission

Not Interested

## Student Poster Contest

Not Interested

**Primary author:** JORKESH, Alireza (Shiraz University)

**Co-authors:** Dr QAJAR, Jafar (Shiraz University); Prof. RIAZI, Masoud (Shiraz University)

**Presenter:** JORKESH, Alireza (Shiraz University)

**Session Classification:** Parallel Session 4

**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 34

Type: **Poster Presentation**

## **A comprehensive investigation of bubble flow regime behavior for equipment optimization and pipeline design**

Bubbly flow is one of the types of gas-liquid two-phase flow regimes, in which the gas phase is dispersed in the liquid phase in the form of small bubbles. This type of flow is usually observed at low gas velocities and high liquid velocities, and it can play an important role in the oil and gas industry. In bubbly flow, the gas bubbles tend to accumulate in the upper part of the pipe due to their lower density compared to the liquid. This non-uniform distribution of the gas phase in the liquid can affect the flow parameters such as pressure drop and mass transfer. Accurate knowledge of the bubbly flow regime and the factors affecting it, such as the gas-to-liquid volume ratio, fluid velocities, and their physical properties, is crucial for the design and optimal operation of industrial equipment like bubble reactors and heat exchangers that utilize this type of flow. Experimental studies and numerical modeling in this field have led to significant progress in understanding and predicting the behavior of bubbly flow. These advancements can contribute to the improvement of the design and efficiency of these industrial equipment. This research aims to provide a comprehensive understanding of the factors influencing the regime transition of bubbly flow, exploring its various applications across different fields, and proposing detection methods. By doing so, a novel perspective for designing, operating, and optimizing the safety and efficiency of pipeline systems will be fulfilled.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** Mr TANHAEI, Hadi (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran); Mr BEHNAM MOTLAGH, Mohammad Amin (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Co-author:** Mr SAEEDI DEHAGHANI, Amir Hossein (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Presenter:** Mr BEHNAM MOTLAGH, Mohammad Amin (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)

**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 35

Type: **Oral Presentation**

## **Simulation study to account for the anisotropy due to oblique fractures in fractured porous media**

The presence of fractures in the fractured porous media requires the use of appropriate numerical methods to consider their effects. The conventional approach in simulating fracture reservoirs is to use the Warren and Root model which assumes a homogeneous medium. In reality, the presence of heterogeneous reservoirs with complex characteristics causes a large deviation in the results of the basic models with the field results. In this work, the method of considering the anisotropy due to the presence of oblique fractures with respect to the flow direction is investigated with a numerical approach. One way to include this factor is to consider the effective correction factor to generalize Warren Root's approach. Modeling is done in COMSOL Multiphysics software, which has been investigated using single-phase and two-phase models. The simulation results under the same boundary conditions and rock and fluid properties show that different equivalent correction coefficients are obtained for fractures with different angles. Examination of the fluid pressure inside the fracture network shows that this equivalent coefficient depends on the fracture orientation, matrix shape and size and the density of the fractures. The results of this study can be used for the suitable simulation of heterogeneous fracture reservoirs.

### **Student presentation contest**

Not Interested

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** Mr ZARE, mohammad**Presenter:** Mr ZARE, mohammad**Track Classification:** Geotechnique/Soil Mechanics



Contribution ID: 36

Type: **Oral Presentation**

## Numerical Simulation of density-driven flow in fractured porous media using extended finite element method

*Tuesday, 24 September 2024 10:30 (15 minutes)*

Understanding mass transport in fractured geological formations is crucial for various applications, including predicting contaminant migration, managing subsurface hydrology, sequestering CO<sub>2</sub> to mitigate climate change, and potentially storing hydrogen for clean energy applications. This study presents a computational model using the eXtended Finite Element Method (X-FEM) to tackle the complexities introduced by variable-density flow within fractured porous media.

Density variations in fluids, arising from temperature differences (thermal buoyancy) or changes in solute concentration (e.g., saltwater intrusion or CO<sub>2</sub>), are the primary driving forces for these phenomena. The model incorporates an advection-diffusion equation to capture various transport regimes (diffusion, dispersion, and advection) while considering these density-driven flow processes. Additionally, the X-FEM effectively handles the discontinuity of material properties across fractures, which can significantly impact flow behavior.

The model's performance is validated by solving benchmark problems (Schincariol and Elder) and a modified Elder problem incorporating fractures. The influence of fracture patterns (horizontal and vertical) and fracture density variations are explored on transport behavior.

This research offers a powerful tool for simulating solute transport in fractured media, considering coupled processes that can further influence flow dynamics. This improved understanding will pave the way for more accurate predictions in environmental and geological applications, such as optimizing geothermal energy extraction and designing safe geological carbon sequestration projects.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Not Interested

**Primary author:** SAEEDMONIR, Saeed (School of Civil Engineering, College of Engineering, University of Tehran, Tehran, Iran.)

**Co-author:** Prof. KHOEI, Amir.R (Department of Civil Engineering, Sharif University of Technology)

**Presenter:** SAEEDMONIR, Saeed (School of Civil Engineering, College of Engineering, University of Tehran, Tehran, Iran.)

**Session Classification:** Parallel Session 3

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 37

Type: **Oral Presentation**

## Smart Proxy Model Development for foam injection in a fractured carbonate reservoir for Enhanced Oil Recovery

*Wednesday, 25 September 2024 11:00 (15 minutes)*

Most of the world's oil reservoirs are carbonate and are often in the secondary stage of production. Foam injection could be a highly effective method for improving displacement efficiency, increasing production rates, and enhancing oil recovery mainly by reducing issues like fingering and channeling during gas-injection based processes. In this study, a fractured carbonate reservoir was simulated using a reservoir simulator to investigate the foam behavior through carbonate, fractured porous media. Sensitivity analysis was performed on key foam injection parameters such as foam viscosity, foam flow rate, oil saturation, and matrix width and height to estimate oil recovery factor. Then, a smart proxy model was developed using two machine learning algorithms, Support Vector Machine (SVM) and Random Forest (RF), to predict oil recovery as a replacement for the complex reservoir simulation model. Among these algorithms, RF showed better performance with a  $R^2$  of 0.9990 and RMSE of 0.2564 for predicting oil recovery. Finally, it was found that the smart proxy model could be used as an alternative to complex fractured carbonate simulation model for predicting and optimizing oil recovery factor using foam injection, reducing the computation time and optimizing the process.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** Ms MAJD TEYMOURI, Hamdam (sahand university of technology)**Co-authors:** Dr CHAHARDOWLI, Mohammad (sahand university of technology); Dr SIMJOO, Mohammad (sahand university of technology)**Presenter:** Ms MAJD TEYMOURI, Hamdam (sahand university of technology)**Session Classification:** Parallel Session 8**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 38

Type: **Poster Presentation**

## Reconstruction of Highly-Heterogeneous Porous Media: Fractured Shale

In the 3D reconstruction of micro CT scan images of porous media for heterogeneous samples (with fractures), the texture of the heterogeneous (fracture) space differs from that of the rock. In this type of problem, a new method should be provided for reconstructing the porous media. Some shale rock samples exhibit fractures of this type, and their reconstruction is considered here. In this research, two artificial intelligence algorithms are employed to reconstruct the pore space of shale. The first algorithm is based on a generative method (a type of generative adversarial neural network) to reconstruct the rock texture space. The second algorithm, which utilizes the output of the first algorithm, attempts to reconstruct the fracture space using a geometry-informed deep learning framework. The reconstruction results indicate a satisfactory level of quality in the reconstruction process.

### Student presentation contest

Not Interested

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Not Interested

**Primary author:** Dr SHAMS, Reza (Sharif University of Technology)**Co-authors:** Prof. MASIHI, Mohsen (Sharif University of Technology); Prof. BLUNT, Martin (Imperial College London); Prof. BOZORGMEHRY BOOZARJOMEHRY, Ramin (Sharif University of Technology)**Presenter:** Dr SHAMS, Reza (Sharif University of Technology)**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 39

Type: **Oral Presentation**

Wednesday, 25 September 2024 10:00 (15 minutes)

[illegible]

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Opt In

**Primary author:** VALIPOUR, Mehdi (Master of Science Student, Sharif University of Technology)

**Co-authors:** Mr JABBARZADEH, Milad (Master of Science, Sharif University of Technology); Mr SADEGHI, Hamed (Associate Professor, Sharif University of Technology)

**Presenter:** VALIPOUR, Mehdi (Master of Science Student, Sharif University of Technology)

**Session Classification:** Parallel Session 6

**Track Classification:** New Energies / Underground Gas Storage



در این مقاله، با استفاده از روش شبکه بولتزمن، شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن انجام شده است. در این روش، سیال به عنوان ذرات در شبکه مدل‌سازی می‌شود و با استفاده از قوانین حرکتی، رفتار آن در شبکه شبیه‌سازی می‌شود. این روش به دلیل سادگی و دقت بالا، برای شبیه‌سازی جریان دو فاز در سنگ مخزن مناسب است. در این مقاله، نتایج شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن ارائه شده است. نتایج نشان می‌دهد که این روش به خوبی قادر به شبیه‌سازی جریان دو فاز در سنگ مخزن است.

### 3. نتایج و بحث

در این بخش، نتایج شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن ارائه شده است. نتایج نشان می‌دهد که این روش به خوبی قادر به شبیه‌سازی جریان دو فاز در سنگ مخزن است. در این روش، سیال به عنوان ذرات در شبکه مدل‌سازی می‌شود و با استفاده از قوانین حرکتی، رفتار آن در شبکه شبیه‌سازی می‌شود. این روش به دلیل سادگی و دقت بالا، برای شبیه‌سازی جریان دو فاز در سنگ مخزن مناسب است. در این مقاله، نتایج شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن ارائه شده است. نتایج نشان می‌دهد که این روش به خوبی قادر به شبیه‌سازی جریان دو فاز در سنگ مخزن است.

a

شکل 3: نتایج شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن

در این شکل، نتایج شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن ارائه شده است. نتایج نشان می‌دهد که این روش به خوبی قادر به شبیه‌سازی جریان دو فاز در سنگ مخزن است. در این روش، سیال به عنوان ذرات در شبکه مدل‌سازی می‌شود و با استفاده از قوانین حرکتی، رفتار آن در شبکه شبیه‌سازی می‌شود. این روش به دلیل سادگی و دقت بالا، برای شبیه‌سازی جریان دو فاز در سنگ مخزن مناسب است. در این مقاله، نتایج شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن ارائه شده است. نتایج نشان می‌دهد که این روش به خوبی قادر به شبیه‌سازی جریان دو فاز در سنگ مخزن است.

شکل 4: نتایج شبیه‌سازی جریان دو فاز در سنگ مخزن با استفاده از روش شبکه بولتزمن

### 1. نتیجه‌گیری

- [1] T. Ramstad, P. E. Oren, S. Bakke, "Simulation of Two Phase Flow in Reservoir Rocks Using a Lattice Boltzmann Method", SPE Journal, 15, 917-927, 2010.
- [2] C. J. Landry, Z. T. Karpyn, O. Ayala, "Relative Permeability of Homogenous-Wet and Mixed-Wet Porous Media as Determined by Pore-Scale Lattice Boltzmann Modeling", Water Resources Research, 50, 3672-3689, 2014.
- [3] F. Hussain, W. V. Pinczewski, Y. Cinar, J. Y. Arns, C. H. Arns & M. L. Turner, "Computation of Relative Permeability from Imaged Fluid Distributions at the Pore Scale", Transport in Porous Media, 104, 91-107, 2014.
- [4] M. J. Blunt, B. Dong, P. Mostaghimi, O. Gharbi, "Pore-Scale Imaging and Modelling", Advances in Water Resources, 51, 197-216, 2013.
- [5] D. Wildenschild, A. P. Sheppard, "X-Ray Imaging and Analysis Techniques for Quantifying Pore-Scale Structure and Processes in Subsurface Porous Media Systems", Advances in Water Resource, 51, 217-246, 2013.
- [6] M. Piller, G. Schena, M. Nolic, S. Favretto, F. Radaelli, E. Rossi, "Analysis of Hydraulic Permeability in Porous Media: from High Resolution X-ray Tomography to Direct Numerical Simulation", Transport in Porous Media 80:57-78, 2009.
- [7] D. D'Humieres, I. Ginzburg, "Viscosity Independent Numerical Errors or Lattice-Boltzmann Models: from Recurrence Equations to Magic Collision Numbers", Computers & Mathematics with Applications 58:823-840, 2009.
- [8] D. B. Silin, T. W. Patzek, "Predicting Relative-Permeability Curves Directly from Rock Images", Proceedings of SPE annual technical conference exhibition, New Orleans, LA, SPE 124974, 2009.

[9] T. Bultreys, J. Van Stappen, J., “Investigating the Relative Permeability Behaviour of Micoporosity-Rich Carbonates and Tight Sandstones with Multi-Scale Pore Network Models”, American Geophysical Union, 2016.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** Mr ZOEIR, Ahmed (Shiraz University)

**Co-authors:** Dr QAJAR, Jafar (Shiraz University); Dr NIKOEE, Ehsan (Shiraz University)

**Presenter:** Mr ZOEIR, Ahmed (Shiraz University)

**Session Classification:** Parallel Session 8

**Track Classification:** Digital Rocks / Machine Learning



Contribution ID: 41

Type: **Poster Presentation**

XXXXXXXXXX XXXXXXXX XXXXXXXX XXXXX XXXXXXXX :XXXXXXXXXX XXXXXXXX XXXXXXXX  
X XXXXXXXX XXXXXXXX XXXXXXXX XXXXXXXX

XX XX XXXXXXX XX XXXXXXX XXXX XXXXXXX XXXXXXX TPMS XXXXXXX XXXXX .XX XXXXXXX XX XXXXXXX XXXXXXX  
XXXXXXXX X XXXXXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX XXXXXXX  
XXXXXXXX XXXX XXXX XXXX XXXXXXX XXXXXXX TPMS X XX XXXXXXX XXXXXXXXXX XXX XXXXXXX XXX XXXXXXX  
XX XXXXXXX XXXX XXXXXXX XXXXXXX X XXXXXXXXXX XXXXXXX XXXX XXXX XXX XXXX .XXXXXXXX XX XXXXXXX XXXXXXX  
XXXXXXXX X XXXXXXXXXX XXXXXXXXXX XXXXXXX XX XXX XXXX XXXX XXX XXXX XXXXXXX .XXXXX

**Student presentation contest**

Opt in

**Journal Submission**

Consider for Journal Submission

**Student Poster Contest**

Opt In

**Primary authors:** BAGHERI, MohammadReza; Ms AHMADI, Sara

**Presenter:** BAGHERI, MohammadReza

**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 43

Type: **Oral Presentation**

XXXXXXXX XX XXXXX XXXXXXXX XX XXXXXXXX XXXXXXXX  
 XXXXXXXX XX XXXXX XX XXXXXXXX XXXXXXXX XX XXXXXXXX XXXXX

*Wednesday, 25 September 2024 10:15 (15 minutes)*

XX XXXXXXXX XXXXX XXXXXXXX X XX XX XXXX XX XXXXXXXX XXXX XXXXXXXX XXXXXXX XXXXXXXX X  
 XXXXXXXX XXXXXXXX XXXXX XX XX XX XXXX XXXXX XXXXX XXXXX XXXXXXXX XX XX XXXXX XXXXXXX  
 XXXXXXXX XX XX XXXXXXX X XXXXXXX XXXXXXX XXXXXXX XX XXXX XXXXXXXXXX XXXXXXX XXXXXXX  
 XXXXXXX XXXXXXX XX XXXXX XXXX XX XX XX XXXX XX XX XX XXXX XXXXX XXXXXXX XXXXX XX  
 XXXXXXX XX XXXXXXX XXXX XXXXXXX X XXXXXXX XX XXXXXXX XXXXXXX XXXX XX XXXXX XX XXXXXXX  
 XXXXX XX XXXXX XXXX XX XXXXXXX XXXXX XXXX XXXXX XX XX XXXXXXX XXXXX XXXXX XX) (XXXXXXXX  
 XXXXX XXXXXXX XX XX XXXXXXX XXXX XXXX XX XXXXXXX XXXXX XXXXX XXXXXXX XXXXX X XXXX XXXXXXX  
 XXXX XXXXXXX XXXXXXX XXXXX XXXXX XXXX XXXX XXXX XXXX XX XXXXXXX XX XXXXXXX XXXXXXX  
 XXXXX XXXXX XXXXX X XXXXXXX XXXX XXXXXXX XX XX XXXXXXX XX XXX XXXX XXXXXXX XXXX XX  
 X(XXXXX XX XX XXXX XX XX XXXXXXX XXXXXXX XX XXXXX XXXXXXX XXXX XXXXXXX XXXXXXX XX XX XXXX  
 XXXX XXXXXXX XXXXX XX XXXXXXX XXXXX XXXX X XX XXXXX XXXXXXX XXXXXXX XXXXXXX XX XXXX XXXXXXX  
 XXXXXXX XXXXXXX XXXXXXX XXXXX XXXX XXXX XXXX XXXXXXX XXXXXXX XX XX XXXXXXX XX XX XXXXXXX  
 XXXXXXX XXXXXXX XXXXXXX XX XX XXXXXXX XXXX XXXXX XXXXXXX XXXXXXX XXXXXXX XXXXX XXXXX  
 XXXXX XXXXXXX XX XX XXXXX XXXX XXXXX XXXXXXX XXXXX XXXXX XXXXX XXXXX XXXXX XXXXX XXXXX

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Opt In

**Primary authors:** Mr NAZARI, Mansour (Sharif University of Technology); Prof. MAHANI, Hassan (Sharif University of Technology); Prof. AYATOLLAHI, Shahab (Sharif University of Technology)

**Presenters:** Mr NAZARI, Mansour (Sharif University of Technology); Prof. MAHANI, Hassan (Sharif University of Technology); Prof. AYATOLLAHI, Shahab (Sharif University of Technology)

**Session Classification:** Parallel Session 6

**Track Classification:** New Energies / Underground Gas Storage

Contribution ID: 44

Type: **Oral Presentation**

## Investigation of the effect of ultrasonic waves on the deposition of asphaltenes in porous media

*Wednesday, 25 September 2024 09:45 (15 minutes)*

Improving oil recovery from reservoirs is an important challenge in the oil industry. In recent years, the use of ultrasonic waves to stimulate oil wells (reducing formation damage) and change the rheological properties of crude oil has received more attention. From the economic, environmental and operational safety perspectives, ultrasonic wave radiation has significant advantages over other conventional methods of improving oil recovery, such as acid injection and hydraulic fracturing. In this regard, the irradiation of ultrasonic waves to crude oil leads to a decrease in oil viscosity and an improvement in the relative permeability of oil in the porous media of rock. The phenomenon of cavitation and vibration created in crude oil are the main factors in changing the properties of crude oil with ultrasonic wave radiation. In this research, the effect of ultrasonic waves on the amount of asphaltene deposition in a transparent porous media micromodel has been investigated. According to the obtained results, irradiation of ultrasonic waves to crude oil has led to a decrease in the amount of asphaltenes deposition in the porous media, and as a result, reduced the blockage of the rock pores. The analysis of the images taken from the micromodel shows that the irradiation of ultrasonic waves to crude oil by breaking the asphaltene clusters in the crude oil prevents their deposition in the rock pores especially near the fracture. The results of this research are used in the improved oil recovery operation from reservoirs with the problem of asphaltene deposition.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** Dr RAZAVIFAR, Mehdi (Faculty of Chemical and Petroleum Engineering, University of Tabriz, Tabriz, Iran)

**Co-authors:** Dr QAJAR, Jafar (Department of Earth Sciences, Faculty of Geosciences, Utrecht University, Utrecht, the Netherlands); Dr RIAZI, Masoud (School of Mining and Geosciences, Nazarbayev University, Astana, Kazakhstan)

**Presenter:** Dr RAZAVIFAR, Mehdi (Faculty of Chemical and Petroleum Engineering, University of Tabriz, Tabriz, Iran)

**Session Classification:** Parallel Session 5

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 45

Type: **Oral Presentation**

XXXXXXXX XX XXXXXX XXXXXX XXXXXX XXXXXX XXXXXXXXXXXX XX XXXXXX  
 XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXXX X XXXXXX XX  
 XXXXXX

*Wednesday, 25 September 2024 11:00 (15 minutes)*

XXXXXXXX XX XXXXXX XXXXXX XXXXXXXXXXX XXXXXX XXXXXX XX XXX XX XXX XXX XXX XX XXX XXXXXX XXXXXX  
 XXXXXXXXXXX XXXX XX XXXX XXXXXXXXXXX XXXXXX XXXXXX XXXX XXXX XXXX XXXX .XXX XXXXXX XXXXXX  
 XXXX XXXXXX XX XXX XXXXXX XXXX XXXXXX XXXXXXXXXXX XXXX XXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXX  
 XXXXXX XXXX XXX X XXXX XXXXXX XX XXX XXXXXXXXXXX XXXXXX XXXX XXX .XXX XX XX XXXXXX XXXXXX  
 XXXXXXXXXXX XXXXXXXXXXX XXXXXX XXXX XX XXXX XXXXXX XX XXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX  
 X XXXXXX XXXXXXXXXXX XXXXXXXXXXX XX XXXX XXXXXXXXXXX XXXX X XXXX XXXX XXX .XXX XXXXXXXXXXX XXXXXXXXXXX  
 XXX XXXXXX XXXXXXXXXXX XX XXX XXXXXX XXX XXXXXXXXXXX X XXXXXXXXXXX XXXXXXXXXXX XXXXXX X XXXXXX XXXX  
 XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX X XXXXXX XXXXXX XXXXXXXXXXX XXXXXXXXXXX .XXX XXX XXXX XXX XXXXXX  
 XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX XXX XXXXXXXXXXX XXXXXX XXXXXX XXXX X XXXXXX XXX XXXXXX XXXXXXXXXXX)  
 (XXXXXXXX XXXXXXXXXXX XXXX XXXXXXXXXXX XX XXXXXX XXX XXXXXX X XXXX XXXXXXXXXXX XXXXXXXXXXX XX .XXX  
 XXX XXXXXX XX XXXXXXXXXXX XX XXXXXX XXX XXXXXXXXXXX XX XXX XXX XXXXXX XXXXXX XXX .XXX XXXXXX XX  
 XXX XXXXXX XXXXXX XXX XXXXXX XXXXXXXXXXX XXXXXX XXXXXX X XXXXXX XX XXX XXXXXXXXXXX XXXXXX XXXX  
 XXX XXXXXX XX XXXX XXXXXXXXXXX XXXXXX X XXXX XXXXXXXXXXX XXXXXXXXXXX .XX XXXXXX XXXXXX XXXX XXX  
 XXX XXXXXX XXXXXXXXXXX XX XXXXXXXXXXX XXXX XXXXXX XXX XXXXXX X XXXXXX XXXXXXXXXXX XX XXXXXX XXXX XXXXXX  
 XX XXXXXX XX XXXXXXXXXXX .XXXXXXXX XXXXXX XXXXXX XXXXXXXXXXX XXXXXXXXXXX XX XXXXXX XX 49/0 X XXXXXX XX  
 XXXXXX XXXX XXXXXX (6 (XXXX X XXXXXX (XXXX) XX XXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX  
 XX .XXXX)

**Student presentation contest**

Opt in

**Journal Submission**

Consider for Journal Submission

**Student Poster Contest**

Opt In

**Primary author:** Mr KHEIROLLAHI, Hossein (Sharif University of Technology)**Co-authors:** Prof. MAHANI, Hassan (Sharif University of Technology); Prof. AYATOLLAHI, Shahab (Sharif University of Technology)**Presenters:** Prof. MAHANI, Hassan (Sharif University of Technology); Mr KHEIROLLAHI, Hossein (Sharif University of Technology); Prof. AYATOLLAHI, Shahab (Sharif University of Technology)**Session Classification:** Parallel Session 10

**Track Classification:** New Energies / Underground Gas Storage

Contribution ID: 46

Type: **Oral Presentation**

## Simulation of Single-Well Chemical Tracer Test (SWCTT) to Measure Residual Oil Saturation

*Wednesday, 25 September 2024 10:00 (15 minutes)*

Determining residual oil saturation (Sor) in hydrocarbon reservoirs is crucial for reservoir evaluation and designing an enhanced oil recovery (EOR) method. Single-well chemical tracer test (SWCTT) is an efficient, economical, and accurate method for estimating Sor within approximately 20 to 30 meters around the well, providing valuable data for production optimization decisions. This technique utilizes the time difference between the production of ester and hydrolyzed alcohol, resulting from the chromatographic separation of the secondary tracer from the partitioning tracer. This study aims to simulate SWCTT for Sor measurement using the University of Texas Chemical Flooding Simulator (UTCHEM) in a glass bead pack flood system. Initially, SWCTT was conducted in this laboratory system by injecting ethyl acetate. Subsequently, an attempt was made to simulate the tracer behavior and experimental results using UTCHEM, a multi-dimensional, multi-phase, and multi-component flooding simulator capable of modeling a separable reactive tracer. The results demonstrated that Simulations by UTCHEM for SWCTT closely match the experimental data from glass bead flooding experiments for Sor estimation. Additionally, sensitivity analyses conducted on key parameters such as diffusion coefficient, injection rate, and tracer concentration revealed that simulation results are sensitive to these parameters. These findings highlight the capability of the SWCTT technique and UTCHEM simulator in accurately evaluating the oil-saturated zone around the well, providing valuable information for reservoir management decisions, including selecting the appropriate EOR fluid and process.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** RAMEZANI GHAFAROKHI, Mostafa (Iran University of Science and Technology (IUST))

**Co-author:** Dr MIRI, Rohaldin (Iran University of Science and Technology (IUST))

**Presenter:** RAMEZANI GHAFAROKHI, Mostafa (Iran University of Science and Technology (IUST))

**Session Classification:** Parallel Session 5

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media



Contribution ID: 47

Type: **Poster Presentation**

## **Pore-scale modeling of non-equilibrium gas injection process in fractured reservoirs**

Many carbonate reservoirs of Iran's Bangestan Group have a tight and fractured matrix. Some of these reservoirs, despite having the conditions for the formation of a gas cap, do not benefit from the gravity drainage mechanism well due to the shortness of the matrices and high capillary pressure. Some of these reservoirs are very undersaturated, and their capillary pressure is usually higher than the oil saturation pressure.

In such reservoirs, the main production mechanism is rock and fluid expansion, which leads to small oil recovery. Despite the high production potential, these reservoirs have more optimal production requirements due to the low recovery factor.

Non-equilibrium gas injection by activating a molecular diffusion mechanism can be an efficient solution to this problem. This study uses the pore-network approach with the aim of accurately modeling this process. In this method, the molecular diffusion process is simulated in a matrix block surrounded by fractures. The developed model also considers the micro-mechanisms of the porous medium drying process.

The main advantage of this model is to pay attention to the microscopic distribution of liquid and gas phases and the arrangement of pores and throats. These features lead to a deeper understanding of the molecular diffusion process and provide a more accurate model for predicting additional production from fractured reservoirs.

This model can be used in choosing the appropriate injection gas, estimating additional production potential, optimizing gas injection flow rate and other parameters related to the molecular diffusion process in fractured reservoirs.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** Mr MEHRPARVAR, Mahdi (Iran University of Science and Technology)

**Co-author:** Dr MIRI, Rohaldin (Iran University of Science and Technology)

**Presenter:** Mr MEHRPARVAR, Mahdi (Iran University of Science and Technology)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 48

Type: **Poster Presentation**

XXXXXXXX XXXX XXX XXXXXX-XXXX XXXXXXXXXXXXXXX XXXXXXX XXXX XXX  
 XXX XXX XXXXXXXXXXXX X XXXXXXXXXXXXXXX

XXXX XXXXXXX XXXX X XXXX XXXXX XXX X XXXXXXXXXXX XXXXXXX XXX XXXXX X XXXXXXX XXX-XXXXXXX  
 XXXX X XXXX XXXX XXX XXXX XXXXXXX XXXXXXX XXXXXXX XXXX XXX X XXXX XXXXX X XXX XXXXX XXXX  
 XXXX XXXX .XXXXXX XXXXXXX XXX XXX XXXXXXX XXX X XXXXXXX XXXXX XXXXXXXXXXXX X XXXXX XXXXXXX  
 XXX XXX XXXXX XXXX .XXXXX XXX XXXXXXX XXX XXXXX XXX XXXXXXX XXXXXXXXXXX XXXXX .XXXXXXX XXXXXXX  
 XXXXXXX XXX XXXX XXXXXXXX X XXXXXXX XXXX XXXXXXX XXX XXXX XXX XXXXX XXXX XXXX XXXXXXX .XXXXXX  
 XXX XXXXXXX XXX XXXXXXX XXXXXXX XXXX XXX XXX XXXX XXXXX XXXXX .XXXXX XXX XXXX XXX XXXXX XXXXX  
 X XXXX XXXXXXX XXX XXXXX XXX XXXXXXXXXXX XXXXXXX XXXXX XXXX XXXXX-XXXX XXXXXXX XXX XXX  
 XXX XXX XXX XXXXX XXXXXXX XXXXXXX XXXX X XXXXXXX XXXXX XXXXX .XXX XXXXX XXX XXXXXXXXXXXXXXX  
 XXXXXXX XXXX XXX XXXXX XXXXX XXX XXX XXX XXXXXXX XXX XXX XXXXXXX XXXX XXX XXXX XXXXXXX  
 XXXX .XXXX XXXXXXX XXX XXXXXXXXXXXXXXX XXXXXXX XXXXXXXX X XXXXXXX XXX XXX XXX XXXXXXX 20 XXX X  
 XXXXX XXX 45 XXXX XXX XXXXX XXXXX XXX 7381 X 8871 XXXXXXX .XXX XXXXXXX XXXXXXX XXX XXXXXXX  
 XXX XXXX XXXXXXX XXX XXXXXXXXXXXXXXX XXXX XXXXX .XX

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Not Interested

**Primary authors:** YAZDA, Farshad; Prof. SADEGHI, Hamed (Associate Professor); Mr ALI-PANAHI, Pouya (Sharif University of Technology)

**Presenter:** YAZDA, Farshad

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 49

Type: **Oral Presentation**

## **Study the effect of fracture roughness on the relative permeability of a fractured porous medium using pore-scale simulations**

*Wednesday, 25 September 2024 10:15 (15 minutes)*

Modeling of flow properties in fractured porous media is important due to the existence of a significant contrast in the storage properties and flow conductivity in the matrix and fracture parts. In the case of two-phase flow, one of the flow properties, which can be affected by fluid flow mechanisms at the pore scale are relative permeability, curves. However, the existence of fracture and the roughness of fracture walls are among the factors that affect these curves. In this research, the micro CT image of a two-dimensional section of rock was used as a basic porous media, and then by adding a horizontal fracture, simulation of a two-phase flow of water and oil was investigated, and two-phase relative permeability curves were extracted by extended JBN method. The simulation of two-phase flow is done using the equations of the phase field method and in the COMSOL software and the effects of parameters such as the width of the fracture and the roughness of the fracture wall on the relative permeability curves of the phases are investigated. The simulation results showed that the presence of a fracture causes a delay in the relative permeability curves. With the increase of the fracture width, the relative permeability values of the phases increase significantly, especially for the wet phase. In addition, the presence of roughness on the fracture surface reduces the relative permeability values of the phases. With the help of the obtained results, a more complete understanding of the flow in the fractured porous media can be obtained.

### **Student presentation contest**

Opt in

### **Journal Submission**

Not Interested

### **Student Poster Contest**

Not Interested

**Primary author:** REZAEI, Parsa**Co-author:** Prof. MASIHI, Mohsen (Co-author)**Presenter:** REZAEI, Parsa**Session Classification:** Parallel Session 5**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 50

Type: **Poster Presentation**

## **Modeling the Damage Caused by Air Penetration During Air Drilling by Using the Lattice Boltzmann Method**

Multiphase flows in porous media are crucial in both industrial processes and natural phenomena, impacting hydrocarbon recovery, groundwater flow, catalysts, and fuel cells. Numerous experimental methods have been developed to study these issues, allowing for large-scale observation of dynamic interface behavior. However, accurately describing fluid flow at the pore scale remains challenging. Laboratory micromodel studies can predict fingering patterns and their initial growth but do not provide insights into their later-stage evolution.

Numerical simulators are valuable for complementing theoretical and experimental studies, examining the effects of flow and physical parameters in complex three-dimensional porous environments. However, continuum-based numerical methods fall short in investigating the impact of pore-scale parameters on bulk properties, failing to detail pore-scale flow patterns. The Lattice Boltzmann Method (LBM) is recognized for its ability to simulate multiphase flows at the pore scale, offering advantages over traditional computational fluid dynamics (CFD) methods due to its parallel computational capability and ease of handling complex geometric boundaries.

In this study, LBM with a phase-field approach was used to investigate formation damage during air drilling, considering high density and viscosity differences. A two-phase simulator core was developed in C++ due to the lack of commercial simulators for this approach. Simulation results were initially validated against theoretical solutions for single-phase and two-phase cases, showing acceptable errors. Further simulations in capillary tubes and synthetic porous media examined flow patterns and the effect of density ratio on these patterns.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Not Interested

**Primary authors:** ZAMANI NOKABADI, Mohammad Hassan (Chemical & Petroleum Engineering Department, Sharif University, Tehran); VASHEGHANI FARAHANI, Mehrdad (Chemical Engineering Department, The University of Manchester, United Kingdom); JAMSHIDI, Saeid (Chemical & Petroleum Engineering Department, Sharif University, Tehran)

**Presenter:** ZAMANI NOKABADI, Mohammad Hassan (Chemical & Petroleum Engineering Department, Sharif University, Tehran)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 51

Type: **Poster Presentation**

## A Review of the Methods for Enhancing Oil Well Production Efficiency

### Abstract:

In a world where crude oil resources are dwindling and the demand for energy is continuously rising, enhanced oil recovery (EOR) technologies have become critically important. While traditional production methods can only recover 30 to 40 percent of the oil present in reservoirs, advanced EOR technologies provide access to substantial amounts of the remaining oil. These technologies, which include a variety of methods such as chemical flooding, water injection, gas injection, steam injection, combustion, and ultrasonic stimulation, significantly improve oil displacement efficiency. This review paper examines these innovative techniques and analyzes their impact on reducing interfacial tension, controlling fluid mobility, and enhancing the efficiency of injected fluids. It also explores miscible and immiscible gas flooding processes as well as steam and combustion injection techniques, each of which, offers different approaches to increasing oil recovery.

**Keywords:** Enhanced oil recovery; Reducing interfacial tension; Chemical injection; Steam injection; Biological injection; Nano material injection

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** MIRAZIZI, zahra (Faculty of civil, water and Environmental Engineering, Shahid Beheshti University in tehran, Iran); Dr ,XXXXXXXX XXXXXX (Faculty of civil, water and Environmental Engineering, Shahid Beheshti University in tehran, Iran)

**Presenter:** MIRAZIZI, zahra (Faculty of civil, water and Environmental Engineering, Shahid Beheshti University in tehran, Iran)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 52

Type: **Poster Presentation**

## Biological soil improvement

The concept of using biological process in soil improvement, which is known as bio-mediated soil improvement, has shown more potential in geotechnical engineering applications in terms of performance and environmental sustainability. This article provides an overview of the soil microorganisms responsible for this process and the factors that affect their metabolic activities and compatibility with the soil, as well as the mechanism of biomineralization. Environmental and other factors that may occur in situ during microbially induced calcite precipitation (MICP) and their effects on the process were identified and presented. Improvements in soil engineering properties such as strength, stiffness and permeability have been investigated as evaluated in some studies.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** Dr POURDEILAMI, Abbas (Assistant Professor)

**Co-authors:** KARAMI, Behfar; Mr PUZESHI, Behzad

**Presenter:** Dr POURDEILAMI, Abbas (Assistant Professor)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 53

Type: **Oral Presentation**

## **Application of statistical analysis of CBCT images in evaluation of rock heterogeneity of hydrocarbon reservoirs and reservoir studies**

*Wednesday, 25 September 2024 11:30 (15 minutes)*

Investigating changes in the reservoir rock's pore system during multiphase flow studies in porous media is crucial, especially for processes like enhanced oil recovery, underground carbon dioxide storage, and wastewater disposal. Ignoring core heterogeneity in laboratory studies can significantly impact the results and their potential for upscaling to the reservoir.

In this study, 31 limestone samples with varying porosity and permeability from the Ilam Formation were scanned using a dental Cone-Beam Computed Tomography (CBCT) scanner. To assess heterogeneity, 9 or 12 cross-sections were selected from each sample. Histograms were plotted for each image based on the CT number of all voxels using image processing software. The standard deviation of each histogram was then calculated. This approach quantified the heterogeneity and classified the samples into five zones based on data dispersion: homogeneous (blue zone), relatively homogeneous (green zone), relatively heterogeneous (yellow zone), heterogeneous (orange zone), and damaged (red zone).

The results showed that out of the 31 samples studied, 14 samples were within the blue zone, 11 in the green zone, 3 in the yellow zone, 1 in the orange zone, and 2 in the red zone. It is recommended to prioritize these samples in that order (1st to 5th) for reservoir rock laboratory studies.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** SAMANI, Shirin (Shiraz University); Mr NASRABADI, Mohsen (National Iranian South Oil Company); Mr HOSSEINZADEH, Saadat (National Iranian South Oil Company); Dr PARSAEI, Rafat (Shiraz University); Dr BAHRAMPOUR, Ehsan (Atra Oral, Maxillofacial Radiology Clinic); Dr ESCROCHI, Mehdi (Shiraz University)

**Presenter:** SAMANI, Shirin (Shiraz University)

**Session Classification:** Parallel Session 8

**Track Classification:** Digital Rocks / Machine Learning



Contribution ID: 54

Type: **Poster Presentation**

## Analytical Investigation of Soil Settlement and Pore Pressure in Poroelastic Systems

### Abstract

This study addresses the analytical solutions for one-dimensional consolidation problems, focusing on classical problems fundamental to geomechanics. Two key problems are examined: Terzaghi's consolidation problem and the loading by fluid pressure in a poroelastic medium. The analysis begins with revisiting Terzaghi's consolidation theory under poroelastic conditions, deriving solutions for pore pressure and settlement. Specifically, the governing equations are transformed into a homogeneous diffusion equation under certain conditions, yielding explicit solutions for both pore pressure and displacement. Subsequently, the impact of an applied fluid pressure on the surface of a soil stratum is explored. Solutions are derived by superposing two loading modes, resulting in comprehensive expressions for pressure and displacement profiles over time. The results elucidate the settlement characteristics and the dissipative nature of energy in these processes. The analytical solutions show that the initial pore pressure distribution is proportional to the applied load and decays over time, while the settlement progresses from an initial value to a final steady state. For the fluid pressure loading case, the surface settlement initially increases and then rebounds, illustrating the complex interaction between pore fluid pressure and soil deformation. This analytical framework not only reinforces the classical consolidation theory but also provides a robust basis for validating numerical models in poroelastic media.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Not Interested

**Primary author:** Ms DAVATGAR, Yeganeh

**Co-author:** Dr ABDOLLAHIPOUR, Abolfazl

**Presenter:** Ms DAVATGAR, Yeganeh

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 55

Type: **Oral Presentation**

## Numerical study of the effect of spatial distribution of artificial rainfall on unsaturated flow in a finite soil slope

*Wednesday, 25 September 2024 11:00 (15 minutes)*

Shallow landslides cause significant financial and human losses annually. Most previous studies have focused on large-scale mountainous slopes, investigating landslides in small-scale urban slopes requires analyzing two-phase flow under rainfall. Therefore, the aim of this study is investigating the effect of local artificial rainfall distribution due to irrigation on unsaturated flow in small-scale soil slopes in different rainfall scenarios. To achieve this goal, a numerical model of a soil slope was created using the multiphase COMSOL software, and artificial rainfall with different spatial distributions was applied in four scenarios. Specifically, rainfall was simulated at the top of the slope, the middle of the slope, the bottom of the slope and the entire boundary. The results showed that the least variation in pore water pressure at the toe of the slope occurs when rainfall is distributed at the upper boundary, and the most critical condition occurs when rainfall is applied to the entire model boundary. These results highlight the role of rainfall spatial distribution in slope stability, especially in agricultural lands and recreational parks where artificial irrigation is common.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Not Interested

**Primary author:** KHOSHOU EI ESFAHANI, Samin Sadat (Master student at Sharif university of technology)

**Co-authors:** TAGHVAEI, Afshin (Master student at sharif university of technology); Dr SADEGHI, Hamed (Sharif University of Technology)

**Presenter:** KHOSHOU EI ESFAHANI, Samin Sadat (Master student at Sharif university of technology)

**Session Classification:** Parallel Session 9

Contribution ID: 56

Type: **Poster Presentation**

## **Leveraging Large Language Models and Generative AI in Pore-Scale Modeling for Enhanced Hydrogen and Carbon Storage**

The transition to sustainable energy sources necessitates advanced technologies for efficient hydrogen and carbon storage. Pore-scale modeling plays a crucial role in understanding the intricate mechanisms within geological formations. This study explores the transformative potential of Large Language Models (LLMs) and Generative Artificial Intelligence (AI) in enhancing pore-scale modeling. A comprehensive overview of traditional pore-scale modeling methods is provided, followed by an examination of recent advancements driven by AI. The capabilities of LLMs and generative AI are highlighted, emphasizing their potential to improve the accuracy of pore-scale simulations, reduce computational costs, and enhance predictive capabilities while reducing the need for extensive physical imaging.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** Mr SHAHIN, Matin (Faculty of Petroleum and Natural Gas Engineering, Sahand University of Technology, Tabriz, Iran)

**Co-author:** Dr SIMJOO, Mohammad (Faculty of Petroleum and Natural Gas Engineering, Sahand University of Technology, Tabriz, Iran)

**Presenter:** Mr SHAHIN, Matin (Faculty of Petroleum and Natural Gas Engineering, Sahand University of Technology, Tabriz, Iran)

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 57

Type: **Oral Presentation**

## **Effect of solvent on porosity, crystallinity and thermal stability of ZIF-8 metal-organic framework**

This study investigated the effect of three different solvents including water, methanol, and ethanol on the structural properties and stability of metal-organic frameworks (MOFs) of ZIF-8 type. The synthesis of ZIF-8 was done using zinc nitrate and 2-methylimidazole in the mentioned solvents, and the characteristics of the synthesized materials were analyzed and compared by XRD, BET, FTIR, and TG analyses. The results show that different solvents significantly affect the percentage of crystallinity, crystal structure, specific surface area, porosity, and thermal stability of ZIF-8. In particular, ZIF-8 synthesized with methanol and ethanol has higher crystallinity and thermal stability than the sample synthesized in the presence of water. The present research findings show that adjusting the synthesis conditions makes it possible to achieve suitable structural, crystalline, and morphological properties of the ZIF-8 metal-organic framework for adsorption and catalyst applications.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** ZAHEDI ASL, saeid (Department of Chemical Engineering, University of Mohaghegh Ardabili); Dr HOORIABAD SABOOR, Fahimeh (Department of Chemical Engineering, University of Mohaghegh Ardabili); Dr SEIFZADEH, Davod (Department of Chemistry, Faculty of Basic Sciences, Mohaghegh Ardabili University)

**Presenter:** ZAHEDI ASL, saeid (Department of Chemical Engineering, University of Mohaghegh Ardabili)

**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 58

Type: **Poster Presentation**

## A Review Study on Lithium Extraction from Geothermal Brine Reservoirs

Alkali metal lithium is recognized as one of the most important and highly valuable metals, utilized extensively in energy production and industry. Among the various sources for lithium extraction, such as seawater, hydrothermal clays, and pegmatites, geothermal brine reservoirs hold significant potential for lithium recovery. However, several challenges impede the development of lithium extraction methods from geothermal reservoirs. These challenges include sustainable production over time, environmental concerns, cost, and appropriate separation techniques. This study briefly addresses the economic challenges of lithium production from geothermal wells, highlighting its potential for long-term, environmentally friendly co-production of geothermal energy and lithium. The findings indicate that at lithium concentrations above 1 gr/L, the extraction efficiency from geothermal brine exceeds 90%. Moreover, lithium extraction using adsorbents demonstrates high efficiency and environmental compatibility.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** Mr OJAGHI, Hamed (Faculty of Petroleum and Natural Gas Engineering, Sahand University of Technology, Tabriz, Iran); SHAHIN, Matin (Faculty of Petroleum and Natural Gas Engineering, Sahand University of Technology, Tabriz, Iran)

**Co-author:** Dr SIMJOO, Mohammad (Faculty of Petroleum and Natural Gas Engineering, Sahand University of Technology, Tabriz, Iran)

**Presenter:** Mr OJAGHI, Hamed (Faculty of Petroleum and Natural Gas Engineering, Sahand University of Technology, Tabriz, Iran)

**Track Classification:** Hydrocarbon Recovery / Flow in Porous Media

Contribution ID: 60

Type: **Oral Presentation**

Wednesday, 25 September 2024 11:15 (15 minutes)

[illegible]

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Not Interested

**Primary authors:** Mr GHOLAMI, Mostafa; ALIPANAHI, Pouya; Dr SADEGHI, Hamed (Sharif University of Technology)

**Presenter:** Mr GHOLAMI, Mostafa

**Session Classification:** Parallel Session 9

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 61

Type: **Oral Presentation**

## Predicting the amount and mechanism of carbon dioxide storage in underground reservoirs using artificial intelligence

*Wednesday, 25 September 2024 11:15 (15 minutes)*

Underground storage of carbon dioxide is one way to reduce the negative effects of greenhouse gas emissions on global climate change. This method was agreed upon as one of the basic solutions to limit global temperature rise to less than 2 degrees Celsius by the end of the 21st century at the UN Convention in December 2015. It is also a strategic method that, on the one hand, enables the continuation of the work of manufacturing plants and Clean Air Control, and on the other hand, helps to establish and maintain the international position of the oil industry and the continuation of oil production, particularly from low-yield reservoirs. Therefore, underground CO<sub>2</sub> storage is not only justifiable but also requires development.

In this paper, the aim is to evaluate the mechanism of absorption and storage of carbon dioxide gas in underground saltwater reservoirs. This mechanism involves the injection of carbon dioxide gas into a reservoir with a saltwater reservoir in which the carbon dioxide gas is mixed with water and remains in the reservoir as a solvent or in an impregnated form. In this project, we simulated 900 different repositories using the Eclipse 300 simulator software, and using the data obtained from the simulation in this software, we trained the artificial intelligence network built using the algorithm (CNN). The network is built using 65,000 parameters for training with a learning rate of 0.1 and has an accuracy of  $R^2=0.98$ . We designed the grid in such a way that 3 parameters—porosity, permeability, and location of the water production well in the reservoir—are predicted in the form of a gray photo, and the rate of injection of carbon dioxide gas and the rate of water production are input as numerical parameters to the grid, resulting in the final storage of carbon dioxide gas.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary author:** AGHABEYG, SAEID**Co-authors:** RAZAVI NEZHAD, Javad; Dr SADEGHNEJAD, Saeid (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran)**Presenter:** AGHABEYG, SAEID

**Session Classification:** Parallel Session 10

**Track Classification:** New Energies / Underground Gas Storage



Contribution ID: 62

Type: **Oral Presentation**

## Generating Images of Naturally Fractured Carbonate Reservoir Rocks Using Deep Learning Architecture

*Wednesday, 25 September 2024 11:45 (15 minutes)*

Carbonated reservoirs is one of the most usable and common reservoirs in throughout the world, especially in the middle east, and it is challenging to predict the fractures in these reservoirs. Generative adversarial networks (GAN) and Autoencoders can generate or create different purposes based on needs using images among different types of artificial intelligence algorithms. Powerful and useful GAN algorithm can generate images similar to the input images, while Autoencoder algorithm encode images into vectors and decode various images. In this study, we want to reconstruct the input 64\*64 pixel resolution images using 2D Autoencoder algorithm and generate images similar to the inputs via GAN algorithm. This resolution speeds up the fracture identification and reduces changes during the training set. We can produce and generate a huge amount of naturally rock fractured carbonated reservoirs images via utilizing a deep GAN which is valuable for increasing and having more images of 2D grayscale images for further analysis in industry and research, including predicting the properties of naturally fractured reservoirs. The loss function of deep GAN algorithm ranges from 0.4 to 1.9 for the generator and from 0.2 to 1.8 for the discriminator. Autoencoder algorithm train and test are converged with the loss function of 0.0015. The images are generated and reconstructed which are convenient to evaluate even by a visual inspection.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** TABRIZIPOUR, Behrad; Dr SADEGHNEZHAD, Saeed**Co-author:** Dr HAJIPOUR SHIRAZI FARD, Mastaneh**Presenter:** TABRIZIPOUR, Behrad**Session Classification:** Parallel Session 8**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 63

Type: **Oral Presentation**

## **Numerical simulations and experimental study of saturated/superheated steam injection into unsaturated zone of soil**

*Wednesday, 25 September 2024 11:30 (15 minutes)*

In this research, two- and three-dimensional simulation of saturated and supersaturated steam injection process in the unsaturated zone of soil is carried out using some simplified assumptions via DuMux Simulator. The simulator is developed in the Department of Hydromechanics and Modeling of Hydrosystems (LH2), Institute for Modeling Hydraulic and Environmental Systems (IWS), Stuttgart University, for Multi-{Phase, Component, Scale, Physics, ...} flow and transport in porous media. The main objective of the study is observation and comparing the progress of the saturated temperature front and the supersaturated temperature front during the process of injecting saturated and supersaturated steam in the unsaturated zone of the soil. Moreover, some experiments are performed for supersaturated and saturated steam injection in the unsaturated zone of soil using the available sand box of Research Facility for Subsurface Remediation, VEGAS, Stuttgart University. Particular purpose of this part of study is evaluation of the heat-up efficiencies of supersaturated steam as opposed to saturated steam. Based on the experimental conditions, values of the local heat-up efficiency are calculated over time concerning the heat-up of defined points in the sandbox. The acquired values are 14.3% and 6.3% for mass based calculated local heat-up efficiency and energy based calculated local heat-up efficiency, respectively.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** JANFADA, Taraneh (Iran University of Science and Technology)**Co-authors:** Prof. KASIRI, Norollah (Computer Aided Process Engineering (CAPE) Laboratory, School of Chemical, Petroleum & Gas Engineering, Iran University of Science and Technology); Prof. CLASS, Holger (Department of Hydromechanics and Modeling of Hydrosystems, Institute for Modelling Hydraulic and Environmental Systems, Stuttgart University)**Presenter:** JANFADA, Taraneh (Iran University of Science and Technology)**Session Classification:** Parallel Session 9

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 64

Type: **Oral Presentation**

## **Comparison of the geotechnical properties of wind-blown sand from the Mesr desert of Iran with three other uniform sands for use in laboratory research.**

*Wednesday, 25 September 2024 11:45 (15 minutes)*

In nature, sandy soils form the major part of alluvial sediments and wind-blown sands on the earth's surface. Examining the different behavioral and resistance characteristics of these types of soils is particularly important in geotechnical engineering. For this purpose, various static and dynamic tests are performed in laboratories using different devices and equipment. These tests can be divided into two groups element and physical model tests. To do both groups, sandy soil samples are needed. Today, natural and artificial sandy soils are used in laboratories worldwide. Several types of sand are used in Iran's current research, among which we can mention the natural and coastal sand of Babolsar and the artificial sand of Firouzkoh. In this article, a windblown sand called Mesr sand, which can be obtained from the Mesr desert of Iran, is introduced. The properties of this sand are compared with those of Babolsar and Firouzkoh, as well as the well-known Toyora sand of Japan, which is a well-known geotechnical sand.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Not Interested

**Primary author:** Mr JAFARZADEH, Fardin (Associate Professor)**Co-authors:** Mrs MOUSAVI, Zahra (Master of science); Mr KARIMZADEH, Ali Akbar (Post-doctoral fellow)**Presenter:** Mr JAFARZADEH, Fardin (Associate Professor)**Session Classification:** Parallel Session 9**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 65

Type: **Poster Presentation**

## **Bibliometric analysis in scientific research on unsaturated soils**

In recent decades, the importance of addressing and understanding the behavior of unsaturated soils has increased due to the challenges of designing safe and cost-effective geotechnical structures based on the axioms of this scientific field. Therefore, this study conducts a bibliometric analysis of research conducted in the field of unsaturated soils in geotechnical engineering. For this purpose, the Vosviewer tool was used to analyze the content of relevant technical literature. The input information and data analysis comprised 2478 articles collected from the Web of Science database. The results show that the highest number of publications occurred in 2022 with 230 articles, accounting for 8.37% of the total dataset. Keyword analysis indicates that terms such as “unsaturated soils” and “model” have the highest frequency, highlighting the complexity of developing devices and testing methods in this area. This study demonstrates significant advancements in methodology and increased attention to unsaturated soil research.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary author:** MOLAABASI, Hossein (Visiting scholar professor, Sharif University of Technology)

**Co-authors:** Dr SADEGHI, Hamed (Sharif University of Technology); Dr SEIF, Mohammad Esmaeil (Islamic Azad University, Arak Branch)

**Presenter:** MOLAABASI, Hossein (Visiting scholar professor, Sharif University of Technology)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 67

Type: **Oral Presentation**

## XXXXXXXX XX XXXXXXXX XXXX XXXXXXX XX XXXXXXX XX XX XX XXXXXXXX XX XXXXXXX XXXX-XXXX XXXXXXXXXXXXXXX **ZIF-8**

XX XX XXXXXXX XXXXXXX XXXXXXX XXXX-XXXX ZIF-8 XXXX XX XXXXXXX XXXXXXX XX XX XXXXXXX XXXX .XXX ZIF-8  
XX XXXX XXXXXXXXXXX XXXXXXX XX XX XX XXXXXXX XXX XXXX XXXXXXX XXXXXXXXXXX XXXXXXX XXXXXXX XX XXXXXXX  
XXXXXXXX XXXX XXXX XXXX XX XX XXXXXXX XXXX XXXXXXX .XXX XXXXXXXXXXX XXX XXXX -XXXX XXXXXXX  
XX XXXXXXX XX XXXXXXX XXXXXXXXXXX XXXXXXXXXXX XX XXXXXXX XXXX pH XXXXX XXXX .XXX  
XXXXXXXX XXXX XXXX XXX ZIF-8 XX XXXX XXXX XXX XXXXXXX XXXX XXXXXXX XXXXXXX XX XX XXXX XXXXXXX  
XXX XXXXXXX XXXX XXXXXXX XXXXXXX .XXX XXX XXXXXXX XXXX XXXXXXX XX ZIF-8 XXXXXXX XX XXXXXXX XX  
XXXX XXXX XXXX XXX XXXXXXXXXXX XXXX XX XXXXXXX XXXXXXX XXXXXXX .XXX XXXXXXX XXXX XXXX XXXX  
XXXXXXXX pH XX XXXX XX XXXXXXXXXXX XXXXXXX XXX .XXXX

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** SEIF ZADEH, Davood; Dr HOOR ABADI SABOR, Fahimeh; Mr ZAHEDI ASL, Saeed

**Presenter:** Dr HOOR ABADI SABOR, Fahimeh

**Track Classification:** Digital Rocks / Machine Learning

Contribution ID: 69

Type: **Poster Presentation**

XXXXXXXXXX XXXXXXXXXXXX XXXXXXXXXXXX XXXXXXXX  
 XXXXXXXXXXXX-XXXXXXXXXXXXXXXX-XXXX XXXXXXXXXXXX XXXXXXXX

XX XX XXXXXX XX XX XXXXXXXXXXXX XX XXXXXX XXXX XX XXXXX XXXXX XXXXXX XXXXXX -XXXXXXXXX  
 -XXXXXXXXX XXXXXXXXXXXX  
 XX XXXXXXXX XXXXXX XXXXX XX .XXX XXXXXXXXXXXX -XXXXXXXXX -XXXXXXXXX XXXXXXXXXXXX X XXXXX XXXXXXXX  
 XXX XXXXXXXX XX XXXX  
 XX XXXXXXXXXXXX XXXXXX XX XXXXX XXXXXXXX XXXXXXXXXXXX .XXXXX XX XXXXXXXXXXXX XX XXXXX XX XXXXXXXXXXXX XX  
 XXXXXX XX XXXXXXXXXXXX  
 XXXXX XX .XXX XXXXXXXXXXXX XXXXX XX XXXXX XXXXXXXXXXXX XX XX XXXXX XXXXXXXX XX XXXX XX XXXXX  
 XXXXXXXXXXXX XX  
 XXXX XX XXXXX XXXX XXXXXX XX XXXXX XX XX XX XXXX XXXXX XXXXXXXXXXXX XXXXXXXX .XXXXX XXXXXXXX  
 XXXXXXXX  
 XXXXXXXX XXXXXXXX XXXXXXXX XXXXXXXX XX XX XXXXXXXX XXXXXXXXXXXX XXXXXXXXXXXX .XXX XXXXX XX XXXX XXXXXXXX  
 XXXX X XXXXX  
 XXXXXXXX XX XX XX XXXXX XXXXX XXXXX XXXXXXXXXXXX XXX XXXX X XXXXXXXXXXXX XXXXXXXX XXXXX XX .XXX  
 XX XX XXXXX XXXXXXXX  
 XXXX XX XXXXXXXX XXXXXXXXXXXX XXX XX XXXXXXXX XX XXXXXXXX .XXXXX XXXXXXXX XX XXXXX XXXXX  
 -XXX XXXX XXXXXXXX  
 XXX XX XXXXX XX XXXXXXXX .XXXXX XX XXXXX XXXXX XXXX XXXXXXXXXXXXXXX XXXXX XXXX XX X XXXXXXXX  
 XXXXX .XXXXX XXXXXXXX X  
 XXX XX XXXXXXXXXXXX XX XXXXXXXXXXXX -XXXXXXXXX -XXXXXXXXX XXXXXXXXXXXX XX XXXXXXXX XXXXXXXX XXXXXXXX XX  
 XX XX XXXX  
 XXXXX XXXX XXXX XX .XXX

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Opt In

**Primary authors:** KHOEI, Amirreza; SAEEDMONIR, Saeed


**Presenters:** KHOEI, Amirreza; SAEEDMONIR, Saeed

**Track Classification:** Geotechnique/Soil Mechanics





Contribution ID: 71

Type: **Oral Presentation***Wednesday, 25 September 2024 11:30 (15 minutes)*

The research presented in this paper focuses on the optimization of energy storage systems for renewable energy sources. The study involves a detailed analysis of various storage technologies, including batteries, supercapacitors, and compressed air energy storage (CAES). The authors propose a novel hybrid storage system that combines the strengths of different technologies to improve efficiency and reduce costs. The research is supported by extensive experimental data and simulation results, demonstrating the feasibility and performance of the proposed system. The findings of this study have significant implications for the development of sustainable energy storage solutions, particularly in the context of grid-scale storage and renewable energy integration. The authors conclude that the proposed hybrid system offers a promising approach to addressing the challenges of energy storage in a decarbonized power system.

### Student presentation contest

Opt in

### Journal Submission

Consider for Journal Submission

### Student Poster Contest

Opt In

**Primary authors:** EMAMI, Mohammad; NOROZI, Mohammad; SAJJADI, Mozhdeh (Assistant Professor)

**Presenter:** NOROZI, Mohammad

**Session Classification:** Parallel Session 10

**Track Classification:** New Energies / Underground Gas Storage

Contribution ID: 72

Type: **Oral Presentation**

## **Improving Oil Recovery: Combination Method of Nanohybrid, Low Salinity Water and Green Surfactant**

*Wednesday, 25 September 2024 10:15 (15 minutes)*

In recent years, a combination of different methods or several materials is used to increase the effectiveness of enhanced oil recovery. When the combination of low salinity water, surfactants and nanoparticles are used simultaneously, it could move more trapped oil and improve the oil recovery factor. Gamma-alumina and silica metal oxide nanoparticles were used because of their high hydrophilic properties. Gum arabic was used as a nanoparticle stabilizer in the presence of salts in basefluids. Gum arabic is a natural and environmentally friendly surfactant and it can also help improve oil recovery by reducing interfacial tension. From distilled water and low salinity water with ppm concentrations (4171, 8142, 20400 and 41710) were considered as base fluids. Different combinations of mass ratio of nanoparticles, salt water and surfactant were investigated. Finally, after checking the stability of solutions, nanofluids with acceptable stability can be identified and selected. In micromodel flooding the highest oil recovery factor related to the gamma-alumina and silica nanohybrid with mass ratio of 10:90 was reported as 60.34%. However, the lowest interfacial tension for the nanohybrid with mass ratio of gamma-alumina and silica of 50:50 dispersed in brine 4171 ppm was reported.

### **Student presentation contest**

Opt in

### **Journal Submission**

Consider for Journal Submission

### **Student Poster Contest**

Opt In

**Primary authors:** KHAJEH KULAKI, Azin; HOSSINI-NASAB, Seyed Mojtaba**Presenters:** KHAJEH KULAKI, Azin; HOSSINI-NASAB, Seyed Mojtaba**Session Classification:** Parallel Session 7**Track Classification:** Diverse Topics in Porous Media

Contribution ID: 73

Type: **Oral Presentation**

The diagram consists of 16 rectangular blocks arranged in three rows. The top row has 8 blocks, the middle row has 16 blocks, and the bottom row has 6 blocks. The blocks are connected by lines, suggesting a flow or sequence. The diagram is labeled 'Figure 1'.

[illegible]

## Student presentation contest

Opt in

## Journal Submission

Consider for Journal Submission

## Student Poster Contest

Opt In

**Primary authors:** MALEKI, Sahar; Dr HOSSEINI-NASAB, Seyed Mojtaba (School of Chemical, Oil and Gas Engineering)

**Presenters:** MALEKI, Sahar; Dr HOSSEINI-NASAB, Seyed Mojtaba (School of Chemical, Oil and Gas Engineering)

**Track Classification:** Geotechnique/Soil Mechanics

Contribution ID: 75

Type: **not specified**

## Exploring the Potential of Energy Piles in Industrial Applications

*Tuesday, 24 September 2024 15:00 (1 hour)*

The impending depletion of fossil fuel resources and the environmental degradation caused by the pollutants generated from their utilization have necessitated the employment, development, and application of renewable energy sources. Geothermal energy, as one of the renewable energy sources, has played a significant role in the development of countries around the world, and in Iran, it is considered one of the most suitable renewable energy sources to potentially replace fossil fuels. Energy piles, a type of structural pile installed beneath the foundation of a structure, incorporate heat exchange pipes within their body, allowing for the absorption and transfer of the Earth's thermal energy by the fluid circulating within these pipes. Essentially, energy piles serve a dual purpose: they function as load-bearing structural members and as an intermediary for harnessing geothermal energy. By employing energy piles, in addition to conserving and stockpiling fossil fuels, their utilization for cooling and heating purposes in the industry can be realized, while simultaneously preventing the release of environmental pollutants that would otherwise result from the combustion of fossil fuels.

In this workshop, the focus will be on the practical usages of energy piles, with discussions on the following subjects:

- 1) An introduction to energy piles
- 2) Geotechnical, structural, and mechanical aspects in implementing energy piles
- 3) An introduction to the Geo-Energy Structures Laboratory at NRI
- 4) Industrial potentials for using energy piles

### Student presentation contest

### Journal Submission

### Student Poster Contest

**Presenter:** Dr AKBARI GARAKANI, Amir

**Session Classification:** Workshop

Contribution ID: 76

Type: **not specified**

## Embark on Your Funding Journey

*Wednesday, 25 September 2024 14:00 (1h 15m)*

“Persuasive Grant Writing” is your guide to using narrative tools that resonate with your funders. Elevate the quality of your grant applications, align your proposals with funder objectives, and apply narrative tools to make your applications more informative and persuasive.

Key Learning Points:

- Craft winning grant applications
- Create effective project budgets
- Design impactful projects
- Uncover the secrets of successful grant revisions

Who Should Attend:

Anyone eager to master the art of finding and applying for grants! Whether you’re a student, a Ph.D. or postdoc, or an early-career researcher, this workshop is tailored just for you.

### Student presentation contest

### Journal Submission

### Student Poster Contest

**Presenter:** SHOKRI, Nima (Hamburg University of Technology)

**Session Classification:** Workshop

Contribution ID: 77

Type: **not specified**

## Patenting or Publishing

*Tuesday, 24 September 2024 11:00 (1 hour)*

Academic researchers often face a dilemma when deciding whether to publish their new research as patents or articles, as the choice between the two options is influenced by various factors that may not always be clear to those in academia. This workshop covers a range of topics, such as the reasons for publishing research papers, the definition and purpose of patents, the requirements for patent eligibility and patentability, the process of patent examination, the differences between authors and inventors, reviewers and examiners, as well as papers and patents. Additionally, the workshop explores the importance of the claim in patents, common reasons for patent rejections, current challenges in the field, provides two examples, and offers a list of 20 points to consider when making the decision between patenting and publishing.

### Student presentation contest

### Journal Submission

### Student Poster Contest

**Presenter:** Dr MAHANI, Hojjat (Assistant Professor, Sharif University of Technology)

**Session Classification:** Workshop

Contribution ID: 78

Type: **not specified**

## Rock 3D Digital Imaging, digital core analysis, and artificial intelligence applications at the pore scale

### Section 1: Physics, instrumentations, and applications of Micro-CT scanners

This workshop introduces the basic physics, instrumentations and applications of Micro-CT scanners. Micro-CT provides micron-sized high-resolution 3D imaging information that cannot be obtained with other non-destructive technologies. This 3D reconstruction allows the user to see inside the object without destroying the structure and produces contrast between different material types depending upon their relative composition and density. This 3D imaging information are used to quantify material characteristics such as porosity, used as input for numerical models, or are simply being used to gain better understanding of the interior of a sample

### Section 2: Imaging techniques to understand pore-scale processes

Dynamic processes such as fluid flow, reactive transport, mineral precipitation, mass transport, and biological activity interact within porous rocks, regulating their macroscopic behavior. These processes are significantly influenced by the rock's mineralogy, pore structure, and environmental conditions. A variety of imaging techniques, such as scanning electron microscopy, laser confocal microscopy, and X-ray computed tomography, have been used to investigate these dynamic pore-scale processes in porous geomaterials. These tools provide valuable insights into the mechanisms occurring within the pores. Understanding these processes through pore-scale imaging and modeling is crucial for accurately predicting the macroscopic behavior of materials. This course briefly introduces a selection of imaging techniques and their potential applications with examples from various experiments related to the visualization and characterization of dynamic pore-scale processes in porous media.

### Section 3: Applications of machine learning in digital rock physics workflow

This workshop investigates into the synergy between machine learning techniques and digital rock physics (DRP) workflow, offering a comprehensive exploration of concepts and applications. The fusion of deep learning methodologies with DRP not only enhances the efficiency of estimating porous media properties but also accelerates the process significantly. The implementation of deep learning is showcased across various applications at the pore scale, encompassing image segmentation (e.g., two-phase (pore-solid) or multimineral segmentation), rock property estimation (regression of single or multiphase properties), image resolution enhancement, and porous media reconstruction. Participants in this course not only gain proficiency in the DRP workflow but also acquire a thorough understanding of the diverse applications of machine learning within this framework. The curriculum spans a broad spectrum, ranging from pore-scale imaging through  $\mu$ -CT scanning to predicting pore-scale properties using DRP. The course explores the latest advancements in pore-scale studies driven by deep learning methods, providing participants with insights into cutting-edge developments in the field.

## Student presentation contest

## Journal Submission

## **Student Poster Contest**

**Presenters:** Dr QAJAR, Jafar (Department of Petroleum Engineering, Shiraz University); Dr SADEGH-NEJAD, Saeid (Department of Petroleum Engineering, Faculty of Chemical Engineering, Tarbiat Modares University, Tehran, Iran); Dr GHADIRI, hossein (Tehran University of Medical Sciences)

**Session Classification:** Workshop



Contribution ID: 79

Type: **not specified**

## **Rock 3D Digital Imaging, digital core analysis, and artificial intelligence applications at the pore scale**

Lab Tour

**Student presentation contest**

**Journal Submission**

**Student Poster Contest**

**Session Classification:** Workshop

